

**PASSENGER AND LIGHT TRUCK
PRODUCT AND DATA GUIDE**

GT

2013

GENERAL TIRE  TM



2013 PRODUCT LINE OVERVIEW.....	3
WARRANTY & UTQG GUIDE	4
DURAGEN TECHNOLOGY	5
3D SIPE TECHNOLOGY	5
MONITOR TECHNOLOGY	6
QUICK REFERENCE GUIDE	7
2013 PRODUCT LINE	
PASSENGER TIRES	
PERFORMANCE	
G-MAX™ AS-03.....	13
ALTIMAX™ HP	17
TOURING	
ALTIMAX™ RT.....	21
LIGHT TRUCK & SUV TIRES	
PERFORMANCE	
GRABBER™ UHP	23
HIGHWAY TERRAIN	
GRABBER™ HTS.....	25
ALL-TERRAIN	
GRABBER™ AT²	29
EXTREME TERRAIN	
GRABBER™	33
WINTER TIRES	
ALTIMAX™ ARCTIC	35
ORIGINAL EQUIPMENT PRODUCT LINES	
AMERITRAC™	40
AMERITRAC™ TR	40
GRABBER™ AW	40
GRABBER™ HTS.....	40
GRABBER™ TR	40
ORIGINAL EQUIPMENT REFERENCE GUIDE.....	41
WARRANTY	43
TIRE TREAD DEPTH CHART	44
TIRE REGISTRATION	46

CTA does not recommend replacing one tire at a time on a vehicle. Fitting a vehicle with an improper mix of tire sizes, constructions, and speed ratings can be dangerous. Consult the vehicle owner's manual to determine proper mixing, matching, or when replacing tires with different sizes, constructions, and speed ratings. If all of the ground tires are not replaced at one time, then at a minimum, CTA recommends replacing all tires on the same axle at one time (see the vehicle owner's manual for 4x4 vehicles for whether there are additional recommendations). This is especially recommended for tires that are listed in this product guide with alternate article numbers. Tires that are identified with alternate article numbers are nearly identical to the tires that they are replacing, but may have slight differences. One difference can be the tread design or pattern which can make the alternate tires incompatible for mixing on the same axle as a different tire.



G-MAX™ AS-03

Dominant ultra-high performance all-season tire delivers precise response in dry and wet conditions with excellent light snow grip.



ALTIMAX™ HP

Smarter high performance all-season tire for today's smarter driver. Designed with quad-tech smart tire technology for exceptional tread life, low noise and ride comfort.



ALTIMAX™ RT

Stylish touring all-season tire supplies a smooth, comfortable ride with excellent treadwear.



GRABBER™ UHP

Bold ultra-high performance all-season light truck, crossover and SUV tire designed for excellent handling and traction in both wet and dry conditions.



GRABBER™ HTS

Strong all-season light truck, crossover and SUV tire provides fuel efficiency with the perfect synergy of comfort, durability and performance.



GRABBER™

Born from competition, this extreme traction tire provides exceptional off-road grip and durability, balanced with on-road driveability.



GRABBER™ AT²

Tough all-terrain tire designed with an aggressive, self-cleaning tread pattern that provides off-road traction, durability and impressive paved road performance.



ALTIMAX™ ARCTIC

Unique grooves and sipes combine with a modern compound to offer outstanding performance in low temperatures.

WARRANTY / UTQG GUIDE

PRODUCT	SEGMENT	SPEED RATING	UTQG	MILEAGE WARRANTY (MILES)	CUSTOMER SATISFACTION TRIAL
G-MAX™ AS-03* (ALL)	PERFORMANCE	V / W	480 A A	40K	45 DAY
ALTIMAX™ HP (H SPEED RATING)	PERFORMANCE	H	440 A A	55K	45 DAY
(V SPEED RATING)	PERFORMANCE	V	440 A A	40K	45 DAY
ALTIMAX™ RT (<= 185 WIDTH, BSW)	TOURING	T	440 A A	70K	45 DAY
(≥ 195 WIDTH, BSW)	TOURING	T	600 A A	70K	45 DAY
(≥ 195 WIDTH, OWL)	TOURING	T	600 A B	70K	45 DAY
GRABBER™ UHP (SERIES ≥ 55)	PERFORMANCE	H / V / W	360 A A	N/A	30 DAY
(SERIES ≤ 50)	PERFORMANCE	H / V / W	320 A A	N/A	30 DAY
GRABBER™ HTS (PASSENGER)	HIGHWAY TERRAIN	Q / R / S / T	640 A B	60K	45 DAY
(PASSENGER)	HIGHWAY TERRAIN	H / V	640 A B	45K	45 DAY
(LT SIZES)	HIGHWAY TERRAIN	Q / R / S	N/A	45K	45 DAY
GRABBER™ (ALL)	EXTREME TERRAIN	Q	N/A	N/A	30 DAY
GRABBER™ AT² (PASSENGER)	ALL-TERRAIN	S / T / H	640 A B +	60K	30 DAY
(LT SIZES)	ALL-TERRAIN	Q / S	N/A	N/A	30 DAY
ALTIMAX™ ARCTIC (ALL)	WINTER	Q	N/A	N/A	30 DAY

*Mileage warranty for the rear axle of split fitments will be 50% of standard tread wear out coverage

+ EXCLUDES 255/55R18 (480 A B)

EDGE DURAGEN

BORN FROM COMPETITION AND ADAPTED FOR THE HIGHWAY.

FEATURE:

ULTRA-HIGH STRENGTH STEEL BELTS, MICRO-FIBER CASING REINFORCEMENTS, AND A BROAD TIRE CONTOUR.

BENEFIT:

ENHANCED STRENGTH AND DURABILITY WITH EVEN TREADWEAR FOR LONGER MILEAGE AND CONFIDENCE IN CHALLENGING CONDITIONS.

AVAILABLE IN:

GRABBER™ HTS
GRABBER™ AT²
GRABBER™



3D SIPLE TECHNOLOGY

INTERLOCKING TREAD BLOCKS.

THE MAGNIFIED IMAGE SHOWS AN OPEN VIEW OF THE SIPLE WITH THE RAISED INTERLOCKING ELEMENT (TOP) AND RECESSED ELEMENT (BELOW).

WHEN INTERLOCKED THE TREAD BLOCKS WORK TOGETHER TO IMPROVE HANDLING AND REDUCE HEAT FOR INCREASED TREADLIFE.



AVAILABLE IN:

GMAX™ AS-03

MONITOR TECHNOLOGY

CONSISTS OF REPLACEMENT TIRE MONITOR TECHNOLOGY (RTM®) AND VISUAL ALIGNMENT INDICATORS (VAI®) TO AID THE CONSUMER IN DETECTING TIRE WEAR.

RTM TECHNOLOGY



THE REPLACEMENT TIRE MONITOR (RTM®) IS AN INDICATOR THAT IS CLEARLY VISIBLE ON THE TIRE'S CENTER RIB.

WHEN THE TIRE WEARS TO 2/32 OF TREAD DEPTH THE INDICATOR TRANSFORMS TO READ "REPLACE TIRE" ALERTING THE DRIVER A TIRE CHANGE IS NEEDED.



AVAILABLE IN:

GMAX™ AS-03
ALTIMAX™ HP

VAI TECHNOLOGY



VEHICLE MISALIGNMENT CAN ADVERSELY AFFECT TIRE WEAR. THE VISUAL ALIGNMENT INDICATORS (VAI®) VISUALLY ALERT THE DRIVER TO VEHICLE MISALIGNMENT ALLOWING A CORRECTION BEFORE TREADLIFE IS COMPROMISED.

VAI® CONSISTS OF SHORT SIPES ON BOTH SHOULDERS OF THE TIRE. WHEN MISALIGNMENT OCCURS ONE OF THESE SIPES WILL WEAR OFF BEFORE THE OTHER ALERTING THE DRIVER TO AN ALIGNMENT CONDITION.



AVAILABLE IN:

GMAX™ AS-03
ALTIMAX™ HP
ALTIMAX™ RT

RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 13	ALTIMAX™ HP PAGE 17	ALTIMAX™ RT PAGE 21	GRABBER™ UHP PAGE 23	GRABBER™ HTS PAGE 25	GRABBER™ AT ² PAGE 29	GRABBER™ PAGE 33	ALTIMAX™ ARTIC PAGE 35	AMERITRAC™ PAGE 40	AMERITRAC™ TR PAGE 40	GRABBER™ AW PAGE 40
13	70	175/70R13		•						•			
		27X8.50R14LT						•					
	70	175/70R14			•								
		185/70R14			•					•			
		195/70R14			•								
		205/70R14			•								
		175/65R14			•					•			
	65	185/65R14	•	•						•			
		195/65R14		•									
		185/60R14	•							•			
60	195/60R14	•											
14	75	30X9.50R15LT						•					
		33X10.50R15LT					•						
		31X10.50R15LT				•	•	•					
		33X12.50R15LT					•	•					
		35X12.50R15LT					•	•					
	205/75R15							•					
	215/75R15							•					
	225/75R15							•					
	235/75R15			•		•							
	P235/75R15											•	
	LT235/75R15					•		•					
	265/75R15					•							
	P265/75R15												
	205/70R15			•	•					•			
	215/70R15			•						•			
	70	225/70R15			•		•		•	•			
		235/70R15			•		•						
255/70R15					•		•						
265/70R15					•		•						
175/65R15		•											
65	185/65R15	•	•						•				
	195/65R15	•	•						•				
	205/65R15	•	•						•				
	215/65R15	•	•						•				
	185/60R15	•	•						•				
60	195/60R15	•	•						•				
	205/60R15	•	•						•				
	215/60R15	•	•						•				
55	195/55R15	•							•				

RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 13	ALTIMAX™ HP PAGE 17	ALTIMAX™ RT PAGE 21	GRABBER™ UHP PAGE 23	GRABBER™ HTS PAGE 25	GRABBER™ AT ² PAGE 29	GRABBER™ PAGE 33	ALTIMAX™ ARTIC PAGE 35	AMERITRAC™ PAGE 40	AMERITRAC™ TR PAGE 40	GRABBER™ AW PAGE 40
85	85	LT215/85R16									•		
		LT235/85R16				•		•	•				
	75	225/75R16				•		•					
		LT225/75R16				•				•			
		235/75R16				•				•			
		245/75R16				•				•			
		P245/75R16											•
		LT245/75R16				•		•	•				
		265/75R16				•			•				
		LT265/75R16				•	•	•	•				
LT285/75R16					•	•	•						
LT295/75R16						•							
70	70	LT315/75R16				•		•					
		215/70R16				•		•	•				
	P215/70R16				•								
	225/70R16				•				•				
	P235/70R16												
	235/70R16				•		•	•					
	245/70R16				•		•	•					
	255/70R16				•		•	•					
	P255/70R16									•			
	265/70R16				•		•	•					
P265/70R16											•		
275/70R16				•									
LT305/70R16						•							
65	65	205/65R16				•							
		215/65R16	•	•				•	•				
		225/65R16	•										
		235/65R16		•			•						
		255/65R16				•	•		•				
60	60	205/60R16	•	•						•			
		215/60R16	•	•						•			
		225/60R16	•	•							•		
		235/60R16	•	•							•		
		195/55R16	•	•							•		
55	55	205/55R16	•	•	•					•			
		215/55R16	•	•							•		
		225/55R16	•	•							•		
50	50	235/55R16	•										
		195/50R16	•										

RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 13	ALTIMAX™ HP PAGE 17	ALTIMAX™ RT PAGE 21	GRABBER™ UHP PAGE 23	GRABBER™ HTS PAGE 25	GRABBER™ AT² PAGE 29	GRABBER™ PAGE 33	ALTIMAX™ ARTIC PAGE 35	AMERITRAC™ PAGE 40	AMERITRAC™ TR PAGE 40	GRABBER™ AW PAGE 40	
16	50	205/50R16	•	•										
		225/50R16	•	•										
		245/50R16		•										
		205/45R16	•											
17	80	33X12.50R17LT					•	•						
		35X12.50R17LT					•	•						
	75	LT235/80R17				•		•	•	•	•			
		235/75R17				•								
	70	LT245/75R17				•								
		235/70R17				•								
		P245/70R17				•			•					
		245/70R17				•		•	•					
		LT245/70R17				•			•					
		P255/70R17									•			
		255/70R17						•						
		P265/70R17				•						•		
		265/70R17						•	•					
		LT265/70R17				•		•	•					
		LT275/70R17												
		LT285/70R17					•			•				
	LT315/70R17					•								
	65	65	215/65R17		•					•				
			225/65R17				•			•				
			235/65R17		•		•			•				
245/65R17						•			•					
255/65R17						•		•						
265/65R17						•		•	•					
P265/65R17												•		
215/60R17				•	•					•				
60	60	225/60R17			•				•					
		255/60R17		•		•								
		275/60R17				•								
55	55	215/55R17	•						•					
		225/55R17	•	•	•				•					
		235/55R17	•	•					•					
		275/55R17				•	•							
50	50	205/50R17	•	•					•					
		215/50R17	•	•	•				•					
		225/50R17	•	•	•									
		235/50R17	•											
		205/45R17	•											

RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 13	ALTIMAX™ HP PAGE 17	ALTIMAX™ RT PAGE 21	GRABBER™ UHP PAGE 23	GRABBER™ HTS PAGE 25	GRABBER™ AT² PAGE 29	GRABBER™ PAGE 33	ALTIMAX™ ARTIC PAGE 35	AMERITRAC™ PAGE 40	AMERITRAC™ TR PAGE 40	GRABBER™ AW PAGE 40	
17	45	245/50R17	•											
		205/45R17	•											
		215/45R17	•	•						•				
		225/45R17	•	•						•				
		235/45R17	•	•						•				
	40	40	245/45R17	•	•									
			255/45R17											
			205/40R17	•	•									
			215/40R17		•									
			245/40R17	•										
18	70	33X12.50R18LT					•	•						
		35X12.50R18LT					•	•						
	65	65	255/70R18				•							
			265/70R18				•		•					
			LT275/70R18				•	•	•					
	60	60	235/65R18			•	•							
			275/65R18						•					
			LT275/65R18				•		•					
			225/60R18		•									
	55	55	235/60R18				•							
			255/60R18				•							
			265/60R18				•							
			275/60R18				•							
			LT285/60R18						•					
			215/55R18			•								
	50	50	235/55R18	•										
			255/55R18				•	•		•				
			225/50R18	•		•								
			235/50R18	•										
			215/45R18	•										
45	45	225/45R18	•											
		235/45R18	•											
		245/45R18	•											
		255/45R18	•											
		215/40R18	•											
40	40	225/40R18	•	•										
		235/40R18	•											
		245/40R18	•											
		255/40R18	•											
		205/40R18	•											

RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 13	ALTIMAX™ HP PAGE 17	ALTIMAX™ RT PAGE 21	GRABBER™ UHP PAGE 23	GRABBER™ HTS PAGE 25	GRABBER™ AT ² PAGE 29	GRABBER™ PAGE 33	ALTIMAX™ ARTIC PAGE 35	AMERITRAC™ PAGE 40	AMERITRAC™ TR PAGE 40	GRABBER™ AW PAGE 40	
18	40	275/40R18	•											
	35	235/35R18	•											
		255/35R18	•											
		265/35R18	•											
		275/35R18	•											
55		255/50R19			•									
19	45	225/45R19	•											
	40	245/45R19	•											
		225/40R19	•											
		245/40R19	•											
		255/40R19	•											
		275/40R19	•											
		225/35R19	•											
		235/35R19	•											
		245/35R19	•											
		255/35R19	•											
		275/35R19	•											
		30	265/30R19	•										
	275/30R19		•											
20		33X12.50R20LT							•					
		35X12.50R20LT					•		•					
	65	LT275/65R20				•								
	60	275/60R20				•								
	55	275/55R20			•	•								
	50	265/50R20												
		285/50R20			•									
		295/50R20			•									
		305/50R20						•						
		LT315/50R20					•							
	45	245/45R20	•											
		255/45R20	•		•									
		275/45R20			•									
		295/45R20			•									
	20	40	245/40R20	•										
275/40R20			•		•									
245/35R20			•											
255/35R20			•											
225/30R20			•											
30	275/30R20	•												

RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 13	ALTIMAX™ HP PAGE 17	ALTIMAX™ RT PAGE 21	GRABBER™ UHP PAGE 23	GRABBER™ HTS PAGE 25	GRABBER™ AT ² PAGE 29	GRABBER™ PAGE 33	ALTIMAX™ ARTIC PAGE 35	AMERITRAC™ PAGE 40	AMERITRAC™ TR PAGE 40	GRABBER™ AW PAGE 40
22	45	305/45R22			•								
	40	265/40R22			•								
		305/40R22			•								
23	40	305/40R23			•								
24	35	305/35R24			•								

G-MAX™ AS-03

DOMINANT ULTRA-HIGH PERFORMANCE ALL-SEASON TIRE DELIVERS PRECISE RESPONSE IN DRY AND WET CONDITIONS WITH EXCELLENT LIGHT SNOW GRIP.

FEATURES: BENEFITS

3D SIPES : WHEN INTERLOCKED THE TREAD BLOCKS WORK TOGETHER TO IMPROVE HANDLING AND REDUCE HEAT FOR INCREASED TREAD LIFE.

V-SHAPED PATTERN WITH AQUA-CLEAVE GROOVE ELEMENTS : CHANNEL AND DIRECT WATER OUT OF THE TREAD FOR EXCELLENT RESISTANCE TO HYDROPLANING.

MONITOR TECHNOLOGY : REPLACEMENT TIRE MONITOR (RTM®) AND VISUAL ALIGNMENT INDICATORS (VAI®) ALERT DRIVERS OF MISALIGNMENT AND TREADWEAR CONDITIONS.

STRAKE GROOVES : EXPOSE MORE BITING EDGES TO ENHANCE TRACTION IN WET AND SNOW CONDITIONS.



TO LEARN MORE ABOUT EXCLUSIVE GENERAL TIRE TECHNOLOGY INCORPORATED INTO THIS TIRE SEE PAGES 5 AND 6 FOR COMPLETE DETAILS AND A SMARTPHONE LINK TO VIDEO.



TREAD: ALL-SEASON, DIRECTIONAL

40000 MILE LIMITED TREADWEAR WARRANTY
** Mileage Warranty for the rear axle of split fitments will be 50% of the standard tread wearout coverage.

45 DAY FREE TRIAL
 visit www.generaltire.com for more info

UTQG: ALL PASSENGER SIZES

TREADWEAR:	480
TRACTION:	A
TEMPERATURE:	A



G-MAX™ AS-03



	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR	
15	55		195/55R15	85V	SL	BSW	15489620000	23.4	16.5	51	7.9 (6.0)	5.5 - 7.0	1279	10	888	NO	
			195/55R16	87V	SL	BSW	15490160000	24.4	17.0	51	7.9 (6.0)	5.5 - 7.0	1202	10	851	NO	
			205/55ZR16	91W	SL	BSW	15489690000	24.9	19.4	51	8.4 (6.5)	5.5 - 7.5	1356	10	834	NO	
			215/55ZR16	93W	SL	BSW	15489740000	25.3	19.6	51	8.9 (7.0)	6.0 - 7.5	1433	10	821	NO	
16	50		225/55ZR16	95W	SL	BSW	15489830000	25.7	20.5	51	9.2 (7.0)	6.0 - 8.0	1521	10	848	NO	
			195/50ZR16	84W	SL	BSW	15489630000	23.7	16.3	51	8.5 (6.0)	5.5 - 7.0	1102	10	877	NO	
			205/50ZR16	87W	SL	BSW	15489670000	24.1	18.2	51	8.4 (6.5)	5.5 - 7.5	1202	10	862	NO	
			225/50ZR16	92W	SL	BSW	15489810000	24.9	20.5	51	9.2 (7.0)	6.0 - 8.0	1389	10	834	NO	
17	45		205/45ZR16	83W	SL	BSW	15489650000	23.3	17.8	51	8.1 (7.0)	6.5 - 7.5	1074	11	892	YES	
			215/55ZR17	94W	SL	BSW	15489750000	26.3	21.1	51	9.2 (7.0)	6.0 - 8.0	1477	10	790	NO	
			225/55ZR17	97W	SL	BSW	15490180000	26.7	21.4	51	9.2 (7.0)	6.0 - 8.0	1609	10	778	NO	
	50			235/55ZR17	99W	SL	BSW	15489910000	27.2	23.0	51	9.6 (7.5)	6.5 - 8.5	1709	10	764	NO
				205/50ZR17	93W	XL	BSW	15489680000	25.1	20.3	51	8.5 (6.5)	5.5 - 7.5	1433	10	828	YES
				215/50ZR17	95W	XL	BSW	15489730000	25.5	20.6	51	8.9 (7.0)	6.0 - 7.5	1521	10	815	YES
				225/50ZR17	94W	SL	BSW	15489820000	25.9	21.3	51	9.2 (7.0)	6.0 - 8.0	1477	10	802	YES
				235/50ZR17	96W	SL	BSW	15489890000	26.3	22.5	51	9.7 (7.5)	6.5 - 8.5	1565	10	790	YES
				245/50ZR17	99W	SL	BSW	15490020000	26.3	24.0	51	9.7 (7.5)	6.5 - 8.5	1709	11	790	YES
	45			205/45ZR17	88W	XL	BSW	15489660000	24.3	17.9	51	8.4 (7.0)	6.5 - 7.5	1235	11	855	YES
				215/45ZR17	91W	XL	BSW	15489710000	24.6	20.7	51	8.5 (7.0)	7.0 - 8.0	1356	11	844	YES
				225/45ZR17	91W	SL	BSW	15489790000	25.0	20.4	51	8.9 (7.5)	7.0 - 8.0	1356	11	831	YES
235/45ZR17				94W	SL	BSW	15489870000	25.3	22.3	51	9.3 (8.0)	7.5 - 9.0	1477	11	821	YES	
245/45ZR17				95W	SL	BSW	15489990000	25.7	23.2	51	9.6 (8.0)	7.0 - 9.0	1521	11	808	YES	
205/40ZR17				84W	XL	BSW	15489640000	23.5	17.1	51	8.4 (7.5)	7.0 - 8.0	1102	10	884	YES	
40			245/40ZR17	91W	SL	BSW	15489950000	24.7	21.6	51	9.8 (8.5)	8.0 - 9.5	1356	10	841	YES	
			255/40ZR17	94W	SL	BSW	15490060000	25.0	23.0	51	10.2 (9.0)	8.5 - 10.0	1477	10	831	YES	
			235/55ZR18	100W	SL	BSW	15489920000	28.2	23.1	51	9.6 (7.5)	6.5 - 8.5	1764	10	737	NO	
			225/50ZR18	95W	SL	BSW	15490170000	26.9	23.8	51	9.2 (7.0)	6.0 - 8.0	1477	10	772	YES	
			235/50ZR18	97W	SL	BSW	15489900000	27.3	23.9	51	9.6 (8.0)	6.5 - 8.5	1609	10	761	YES	
			215/45ZR18	93W	XL	BSW	15489720000	25.6	20.6	51	8.4 (7.0)	7.0 - 8.0	1433	11	811	YES	
18	45		225/45ZR18	91W	SL	BSW	15489800000	26.0	22.3	51	8.9 (7.5)	7.0 - 8.5	1356	11	799	YES	
			235/45ZR18	98W	XL	BSW	15489880000	26.3	21.3	51	9.3 (8.0)	7.5 - 9.0	1654	11	790	YES	
			245/45ZR18	100W	XL	BSW	15494190000	26.7	23.3	51	9.6 (8.0)	7.5 - 9.0	1764	11	778	YES	
	40			255/45ZR18	103W	XL	BSW	15490090000	27.0	24.4	51	10.0 (8.5)	8.0 - 9.5	1929	11	769	YES
				215/40ZR18	89W	XL	BSW	15489700000	24.8	19.5	51	8.6 (7.5)	7.0 - 8.5	1279	10	838	YES
				225/40ZR18	92W	XL	BSW	15489770000	25.1	20.1	51	9.0 (8.0)	7.5 - 9.0	1389	10	828	YES
35			235/40ZR18	95W	XL	BSW	15494160000	25.4	21.9	51	9.5 (8.5)	8.0 - 9.5	1477	10	818	YES	
			245/40ZR18	97W	XL	BSW	15494170000	25.7	22.8	51	9.8 (8.5)	8.0 - 9.5	1609	10	808	YES	
			255/40ZR18	99W	XL	BSW	15490070000	26.0	23.3	51	10.2 (9.0)	8.5 - 10.0	1709	10	799	YES	
35			275/40ZR18	99W	SL	BSW	15490140000	26.7	25.0	51	10.9 (9.5)	9.0 - 11.0	1709	10	778	YES	
			255/35ZR18	94W	XL	BSW	15494200000	25.0	22.5	51	10.0 (9.0)	8.5 - 10.0	1477	10	831	YES	

New size for 2012 Second Edition

Continued next page

PASSENGER TIRES / PERFORMANCE / G-MAX™ AS-03

G-MAX™ AS-03

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
18	35	265/35ZR18	97W	XL	BSW	15490110000	25.3	22.6	51	10.7 (9.5)	9.0 - 10.5	1609	10	821	YES
		275/35ZR18	95W	SL	BSW	15490130000	25.6	24.4	51	11.2 (9.5)	9.0 - 11.0	1521	10	811	YES
19	45	225/45ZR19	92W	SL	BSW	15490350000	27.4	22.1	51	9.6 (8.0)	7.0 - 8.5	1389	11	758	YES
		245/45ZR19	98W	SL	BSW	15490010000	27.7	24.1	51	9.6 (8.0)	7.5 - 9.0	1654	11	750	YES
	40	225/40ZR19	93W	XL	BSW	15489780000	26.1	21.4	51	9.1 (8.0)	7.5 - 9.0	1279	10	796	YES
		245/40ZR19	98W	XL	BSW	15494180000	26.7	23.0	51	9.8 (8.5)	8.0 - 9.5	1654	10	778	YES
		255/40ZR19	100W	XL	BSW	15490080000	27.0	24.9	51	10.2 (9.0)	8.5 - 10.0	1764	10	769	YES
		275/40ZR19	101W	SL	BSW	15490150000	27.7	28.7	51	11.1 (9.5)	9.0 - 11.0	1819	10	750	YES
	35	225/35ZR19	88W	XL	BSW	15489760000	25.2	19.7	51	9.1 (8.0)	7.5 - 9.0	1235	10	824	YES
		235/35ZR19	91W	XL	BSW	15489850000	25.5	21.4	51	9.5 (8.5)	8.0 - 9.5	1356	10	815	YES
		245/35ZR19	93W	XL	BSW	15489930000	25.8	21.0	51	9.8 (8.5)	8.0 - 9.9	1433	10	805	YES
		255/35ZR19	96W	XL	BSW	15490040000	26.0	23.0	51	10.3 (9.0)	8.5 - 10.0	1565	10	799	YES
		275/35ZR19	100W	XL	BSW	15490320000	26.6	26.1	51	10.5 (9.5)	9.0 - 11.0	1764	10	781	YES
		275/35ZR19	100W	XL	BSW	15490320000	26.6	26.1	51	10.5 (9.5)	9.0 - 11.0	1764	10	781	YES
	30	265/30ZR19	93W	XL	BSW	15490100000	25.3	21.9	51	10.7 (9.5)	9.0 - 10.0	1433	10	821	YES
		275/30ZR19	96W	XL	BSW	15490120000	25.5	23.7	51	10.9 (9.5)	9.0 - 10.0	1565	10	815	YES
20	45	245/45ZR20	103W	XL	BSW	15490360000	28.7	24.8	51	9.6 (8.0)	7.5 - 9.0	1929	11	724	YES
		255/45ZR20	105W	XL	BSW	15490340000	29.0	27.6	51	10.0 (8.5)	8.0 - 9.5	2039	10	716	YES
	40	245/40ZR20	99W	XL	BSW	15489980000	27.7	26.2	51	9.8 (8.5)	8.0 - 9.5	1709	10	750	YES
		275/40ZR20	106W	XL	BSW	15490330000	28.7	28.5	51	10.9 (9.5)	9.0 - 10.5	2094	10	724	YES
	35	245/35ZR20	95W	XL	BSW	15489940000	26.8	22.8	51	9.6 (8.5)	8.0 - 9.5	1521	10	775	YES
		255/35ZR20	97W	XL	BSW	15490050000	27.0	24.4	51	10.2 (9.0)	8.0 - 10.0	1609	10	769	YES
	30	275/30ZR20	97W	XL	BSW	15490380000	26.5	24.0	51	10.4 (9.5)	9.0 - 10.0	1609	10	784	YES

245/40ZR19 New size for 2012 Second Edition



ALTIMAX™ HP

SMARTER HIGH PERFORMANCE ALL-SEASON TIRE FOR TODAY'S SMARTER DRIVER. DESIGNED WITH QUAD-TECH SMART TIRE TECHNOLOGY FOR EXCEPTIONAL TREAD LIFE, LOW NOISE AND RIDE COMFORT

FEATURES: BENEFITS

MONITOR TECHNOLOGY : REPLACEMENT TIRE MONITOR (RTM®) AND VISUAL ALIGNMENT INDICATORS (VAI®) ALERT DRIVERS OF MISALIGNMENT AND TREADWEAR CONDITIONS.

ACOUSTIC MODULATION SOUND TECHNOLOGY (AMST) : SOUND WAVE SUPPRESSION TECHNOLOGY THAT WORKS TO REDUCE ROAD TIRE NOISE FOR A QUIET RIDE.

TWIN CUSHION SILICA TREAD COMPOUND : HIGH AND LOW DENSITY TREAD COMPOSITES DELIVER EXTRAORDINARY RIDE COMFORT.

REACTIVE CONTOUR TECHNOLOGY : REACTS TO DIFFERING ROAD CONDITIONS TO MAINTAIN CONTACT WITH ROAD SURFACE FOR INCREASED DRIVING CONFIDENCE.



TO LEARN MORE ABOUT EXCLUSIVE GENERAL TIRE TECHNOLOGY INCORPORATED INTO THIS TIRE SEE PAGE 6 FOR COMPLETE DETAILS AND A SMARTPHONE LINK TO VIDEO.



TREAD: ALL-SEASON, DIRECTIONAL

55000 MILE LIMITED TREADWEAR WARRANTY
All H Rated.

40000 MILE LIMITED TREADWEAR WARRANTY
All V Rated.

45 DAY FREE TRIAL
visit www.generaltire.com for more info

UTQG:	ALL SIZES
TREADWEAR:	440
TRACTION:	A
TEMPERATURE:	A



ALTIMAX™ HP



	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
14	65	185/65R14	86H SL BSW 15480910000	23.5	15.7	51	7.4 (5.5)	5.0 - 6.5	1168	10	884	NO				
			185/60R14	82H SL BSW 15480880000	22.7	15.2	51	7.4 (5.5)	5.0 - 6.5	1047	10	915	NO			
	60	195/60R14	86H SL BSW 15480940000	23.2	15.7	51	7.9 (6.0)	5.5 - 7.0	1168	10	895	NO				
15	65	175/65R15	84H SL BSW 15516460000	24.0	14.0	51	7.2 (5.0)	5.0 - 6.0	1102	10	866	NO				
			185/65R15	88H SL BSW 15480670000	24.5	16.3	51	7.4 (5.5)	5.0 - 6.5	1235	10	848	NO			
			195/65R15	91H SL BSW 15480590000	25.0	17.5	51	7.9 (6.0)	5.5 - 7.0	1356	10	831	NO			
	60	205/65R15	94H SL BSW 15480530000	25.5	17.8	51	8.2 (6.0)	5.5 - 7.5	1477	10	815	NO				
			185/60R15	88H XL BSW 15480980000	23.7	16.0	51	7.4 (5.5)	5.0 - 6.5	1235	10	877	NO			
			195/60R15	88V SL BSW 15480620000	24.2	16.7	51	8.0 (6.0)	5.0 - 7.0	1235	10	858	NO			
		195/60R15	88H SL BSW 15480630000	24.2	17.1	51	8.0 (6.0)	5.0 - 7.0	1235	10	858	NO				
		205/60R15	91H SL BSW 15480550000	24.7	17.4	51	8.2 (6.0)	5.5 - 7.5	1356	10	841	NO				
		215/60R15	94H SL BSW 15480520000	25.2	20.3	51	8.7 (6.5)	6.0 - 7.5	1477	10	824	NO				
16	65	215/65R16	98H SL BSW 15484360000	27.0	21.3	51	8.7 (6.5)	6.0 - 7.5	1654	10	769	NO				
			225/65R16	100H SL BSW 15488160000	27.5	23.2	51	9.0 (6.5)	6.0 - 7.0	1764	10	755	NO			
			205/60R16	92V SL BSW 15441590000	25.7	19.5	51	8.2 (6.0)	5.5 - 7.5	1389	10	808	NO			
	60	205/60R16	92H SL BSW 15484150000	25.7	18.8	51	8.2 (6.0)	5.5 - 7.5	1389	10	808	NO				
			215/60R16	95V SL BSW 15441600000	26.2	20.5	51	8.7 (6.5)	6.0 - 7.5	1521	10	793	NO			
			215/60R16	95H SL BSW 15484180000	26.2	20.4	51	8.7 (6.5)	6.0 - 7.5	1521	10	793	NO			
		225/60R16	98V SL BSW 15441690000	26.6	21.2	51	9.0 (6.5)	6.0 - 8.0	1654	10	781	NO				
		225/60R16	98H SL BSW 15484230000	26.6	21.1	51	9.0 (6.5)	6.0 - 8.0	1654	10	781	NO				
		235/60R16	100H SL BSW 15488090000	27.1	24.4	51	9.4 (7.0)	6.5 - 8.5	1764	10	767	NO				
	55	195/55R16	87H SL BSW 15489360000	24.4	16.9	51	7.9 (6.0)	5.5 - 7.0	1202	10	851	NO				
			205/55R16	91H SL BSW 15484120000	24.9	18.6	51	8.4 (6.5)	5.5 - 7.5	1356	10	834	NO			
			215/55R16	93H SL BSW 15484160000	25.3	20.6	51	8.9 (7.0)	6.0 - 7.5	1433	10	821	NO			
		215/55R16	93V SL BSW 15489350000	25.3	20.1	51	8.9 (7.0)	6.0 - 7.5	1433	10	821	NO				
		225/55R16	95H SL BSW 15484210000	25.7	21.1	51	9.2 (7.0)	6.0 - 8.0	1521	10	808	NO				
		235/55R16	98H SL BSW 15488180000	26.2	22.0	51	9.7 (7.5)	6.5 - 8.5	1654	10	793	NO				
	50	205/50R16	87H SL BSW 15480490000	24.1	18.4	51	8.4 (6.5)	5.5 - 7.5	1202	10	862	NO				
			225/50R16	92H SL BSW 15484190000	24.9	21.6	51	9.2 (7.0)	6.0 - 8.0	1389	10	834	NO			
			245/50R16	97H SL BSW 15484240000	25.6	22.6	51	10.0 (7.5)	7.0 - 8.5	1609	11	811	NO			
17	65	235/65R17	104H SL BSW 15488100000	29.0	27.5	51	9.4 (7.0)	6.5 - 8.5	1984	10	716	NO				
			215/60R17	96H SL BSW 15488130000	27.2	21.2	51	9.3 (6.5)	6.0 - 7.5	1565	10	764	NO			
	60	255/60R17	106H SL BSW 15488110000	29.0	32.4	51	10.2 (7.5)	7.0 - 9.0	2094	11	716	NO				
			225/55R17	97H SL BSW 15484320000	26.7	23.2	51	9.2 (7.0)	6.0 - 8.0	1609	10	778	NO			
	55	235/55R17	99H SL BSW 15484390000	27.2	23.9	51	9.6 (7.5)	6.5 - 8.5	1709	10	764	NO				
			205/50R17	93H XL BSW 15484990000	25.1	20.5	51	8.4 (6.5)	5.5 - 7.5	1433	10	828	YES			
	50	215/50R17	91H SL BSW 15484290000	25.5	19.9	51	8.9 (7.0)	6.0 - 7.5	1356	10	815	YES				
			225/50R17	94H SL BSW 15483630000	25.9	22.4	51	9.2 (7.0)	6.0 - 8.0	1477	10	802	YES			
			215/45R17	87H SL BSW 15484270000	24.6	17.6	51	8.5 (7.0)	7.0 - 8.0	1202	11	844	YES			
	45	225/45R17	91H SL BSW 15448320000	25.0	19.7	51	8.9 (7.5)	7.0 - 8.5	1356	10	831	YES				

Continued next page

PASSENGER TIRES / PERFORMANCE / ALTIMAX™ HP

ALTIMAX™ HP

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
17	45	235/45R17	94H	SL	BSW	15516700000	25.3	21.9	51	9.3 (8.0)	7.5 - 9.0	1477	11	821	YES
		245/45R17	95H	SL	BSW	15484340000	25.7	22.1	51	9.6 (8.0)	7.0 - 9.0	1521	11	808	YES
	40	205/40R17	80H	SL	BSW	15484250000	23.5	16.9	51	8.4 (7.5)	7.0 - 8.0	992	10	884	YES
		215/40R17	83H	SL	BSW	15484260000	23.8	17.3	51	8.6 (7.5)	7.0 - 8.5	1074	10	873	YES
18	60	225/60R18	100H	SL	BSW	15484380000	28.6	23.4	51	9.0 (6.5)	6.0 - 8.0	1764	10	726	NO
	40	225/40R18	92H	XL	BSW	15516670000	25.1	20.5	51	9.0 (8.0)	7.5 - 9.0	1389	10	828	YES



ALTIMAX™ RT

STYLISH TOURING ALL-SEASON TIRE SUPPLIES A SMOOTH, COMFORTABLE RIDE WITH EXCELLENT TREADWEAR.

FEATURES: BENEFITS

VISUAL ALIGNMENT INDICATORS (VAI®) : EXTENDS THE LIFE OF THE TIRE BY VISUALLY ALERTING YOU TO VEHICLE MISALIGNMENT.

ACOUSTIC MODULATION SOUND TECHNOLOGY (AMST) : SOUND WAVE SUPPRESSION TECHNOLOGY THAT WORKS TO REDUCE ROAD TIRE NOISE FOR A QUIET RIDE .

TWIN CUSHION SILICA TREAD COMPOUND : HIGH AND LOW DENSITY TREAD DELIVERS EXTRAORDINARY RIDE COMFORT.

REACTIVE CONTOUR TECHNOLOGY : REACTS TO DIFFERENT ROAD CONDITIONS TO MAINTAIN CONTACT WITH THE ROAD SURFACE.



TO LEARN MORE ABOUT EXCLUSIVE GENERAL TIRE TECHNOLOGY INCORPORATED INTO THIS TIRE SEE PAGE 6 FOR COMPLETE DETAILS AND A SMARTPHONE LINK TO VIDEO.



TREAD: ALL-SEASON, SYMMETRIC

70000 MILE LIMITED TREADWEAR WARRANTY

45 DAY FREE TRIAL
visit www.generaltire.com for more info

UTQG:	≤185 WIDTH	≥195 WIDTH
TREADWEAR:	440	600
TRACTION:	A	A
TEMPERATURE:	A	A*

*Excluding OWL. OWL=B

ALTIMAX™ RT



	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
13	70		175/70R13	82T SL BSW	15480770000	22.6	13.5	44	7.0 (5.0)	4.5 - 6.0	1047	11	919	NO		
			175/70R14	84T SL BSW	15480850000	23.6	13.5	44	7.0 (5.0)	4.5 - 6.0	1102	10	880	NO		
14	70		185/70R14	88T SL BSW	15483670000	24.2	16.0	44	7.4 (5.5)	4.5 - 6.0	1235	11	858	NO		
			195/70R14	91T SL BSW	15488710000	24.7	17.3	44	7.9 (6.0)	5.0 - 6.5	1356	11	841	NO		
			205/70R14	98T XL BSW	15480960000	25.3	20.5	51	8.2 (6.0)	5.0 - 7.0	1654	11	821	NO		
			175/65R14	82T SL BSW	15448290000	23.0	14.0	44	7.0 (5.0)	5.0 - 6.0	1047	11	903	NO		
65			185/65R14	86T SL BSW	15483660000	23.5	15.2	44	7.4 (5.5)	5.0 - 6.5	1168	11	884	NO		
			195/65R14	89T SL BSW	15484410000	24.0	16.1	44	7.9 (6.0)	5.5 - 7.0	1279	11	866	NO		
			235/75R15	105T SL OWL	15488000000	28.9	29.9	44	9.3 (6.5)	6.0 - 8.0	2039	12	719	NO		
70			205/70R15	96T SL BSW	15488720000	26.3	19.3	44	8.2 (6.0)	5.0 - 7.0	1565	11	790	NO		
			215/70R15	98T SL BSW	15480510000	26.9	21.0	44	8.7 (6.5)	5.5 - 7.0	1654	12	772	NO		
			225/70R15	100T SL OWL	15488170000	27.4	26.5	44	9.0 (6.5)	6.0 - 7.5	1764	12	758	NO		
			235/70R15	103T SL OWL	15488210000	28.0	29.2	44	9.4 (7.0)	6.0 - 8.0	1929	12	742	NO		
65			185/65R15	88T SL BSW	15480690000	24.5	16.6	44	7.4 (5.5)	5.0 - 6.5	1235	11	848	NO		
			195/65R15	91T SL BSW	15480610000	25.0	17.5	44	7.9 (6.0)	5.5 - 7.0	1356	11	831	NO		
			205/65R15	94T SL BSW	15441570000	25.5	18.3	44	8.2 (6.0)	5.5 - 7.5	1477	11	815	NO		
			215/65R15	96T SL BSW	15480870000	26.0	20.5	44	8.7 (6.5)	6.0 - 7.5	1565	11	799	NO		
60			185/60R15	84T SL BSW	15480540000	23.7	16.0	44	7.4 (5.5)	5.0 - 6.5	1102	11	877	NO		
			195/60R15	88T SL BSW	15480930000	24.2	17.9	44	8.0 (6.0)	5.0 - 7.0	1235	11	858	NO		
			205/60R15	91T SL BSW	15480560000	24.7	18.4	44	8.2 (6.0)	5.5 - 7.5	1356	11	841	NO		
			215/60R15	94T SL BSW	15484430000	25.2	20.2	44	8.7 (6.5)	6.0 - 7.5	1477	11	824	NO		
65			205/65R16	95T SL BSW	15480840000	26.5	20.0	44	8.5 (6.0)	5.5 - 6.5	1521	11	784	NO		
			215/65R16	98T SL BSW	15484450000	27.0	22.0	44	8.7 (6.5)	6.0 - 7.5	1654	11	769	NO		
			235/65R16	103T SL BSW	15488200000	28.0	25.5	44	9.4 (7.0)	6.5 - 7.5	1929	11	742	NO		
			205/60R16	92T SL BSW	15484470000	25.7	19.9	44	8.2 (6.0)	5.5 - 7.5	1389	11	808	NO		
			215/60R16	95T SL BSW	15484440000	26.2	21.0	44	8.7 (6.5)	6.0 - 7.5	1521	11	793	NO		
			225/60R16	98T SL BSW	15481010000	26.6	23.0	44	9.0 (6.5)	6.0 - 8.0	1654	11	781	NO		
55			235/60R16	100T SL BSW	15488080000	27.1	25.4	44	9.4 (7.0)	6.5 - 8.5	1764	11	767	NO		
			205/55R16	91T SL BSW	15480650000	24.9	19.2	44	8.4 (6.5)	5.5 - 7.5	1356	11	834	NO		
			215/65R17	99T SL BSW	15488140000	28.0	22.7	44	8.7 (6.5)	6.0 - 7.5	1709	11	742	NO		
60			215/60R17	96T SL BSW	15488120000	27.2	22.5	44	9.3 (6.5)	6.0 - 7.5	1565	11	764	NO		
			225/60R17	99T SL BSW	15484370000	27.6	23.6	44	9.0 (6.5)	6.0 - 8.0	1709	11	753	NO		
			225/55R17	97T SL BSW	15488150000	26.7	23.3	44	9.2 (7.0)	6.0 - 8.0	1609	11	778	NO		
			215/50R17	91T SL BSW	15516760000	25.5	20.4	44	8.9 (7.0)	6.0 - 7.5	1356	10	815	NO		
50			225/50R17	94T SL BSW	15483610000	25.9	21.9	44	9.2 (7.0)	6.0 - 8.0	1477	10	802	NO		
			235/65R18	106T SL BSW	15483620000	30.0	31.1	44	9.4 (7.0)	6.5 - 8.5	2095	10	692	NO		
55			215/55R18	95T SL BSW	15483590000	27.3	23.1	44	8.9 (7.0)	6.0 - 7.5	1521	10	761	NO		
			225/50R18	95T SL BSW	15516770000	26.9	23.5	44	9.2 (7.0)	6.0 - 8.0	1477	11	772	NO		

PASSENGER TIRES / TOURING / ALTIMAX™ RT



GRABBER™ UHP

BOLD ULTRA-HIGH PERFORMANCE ALL-SEASON LIGHT TRUCK, CROSSOVER AND SUV TIRE DESIGNED FOR EXCELLENT HANDLING AND TRACTION IN BOTH WET AND DRY CONDITIONS.

SECOND GENERATION SILICA TREAD COMPOUND : DELIVERS EXCELLENT HANDLING, BRAKING AND TRACTION IN ALL CONDITIONS.

V-SHAPED DIRECTIONAL TREAD WITH GROOVES FROM CENTER TO SHOULDER : AIDS IN EFFICIENT WATER EVACUATION AND IMPROVES ROAD CONTACT FOR CONTROL IN WET CONDITIONS.

FLAT BELT CONTOUR, SHALLOW SLOTS AND INCREASED TREAD DEPTH IN SHOULDER AREA : WORK TOGETHER TO DELIVER EVEN WEAR AND EXTENDED TREAD LIFE.

ADVANCED SOUND REDUCTION TECHNOLOGY AND CONTINUOUSLY VARYING GROOVE ANGLES : HELPS ASSURE AN INCREDIBLY QUIET, COMFORTABLE RIDE.



TREAD: ALL-SEASON, DIRECTIONAL

30 DAY FREE TRIAL
visit www.generaltire.com for more info

UTQG:	SERIES ≥ 55	SERIES ≤ 50
TREADWEAR:	360	320
TRACTION:	A	A
TEMPERATURE:	A	A

GRABBER™ UHP



	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
16	65		255/65R16	109H	SL	BSW	15477130000	29.1	34.5	51	10.2 (7.5)	7.0 - 9.0	2271	11	714	YES
17	60		255/60R17	106V	SL	BSW	15477170000	29.0	32.3	51	10.2 (7.5)	7.0 - 9.0	2094	11	716	YES
	55		275/55R17	109V	SL	BSW	15477210000	28.9	33.6	51	11.2 (8.5)	7.5 - 9.5	2271	10	719	YES
18	60		235/60R18	107V	XL	BSW	15478900000	29.1	26.9	51	9.4 (7.0)	6.5 - 8.5	2150	10	714	YES
	55		255/55R18	109W	XL	BSW	15477200000	29.0	30.5	51	10.4 (8.0)	7.0 - 9.0	2271	10	716	YES
19	50		255/50R19	107W	XL	BSW	15484090000	29.0	30.0	51	10.4 (8.0)	7.0 - 9.0	2150	10	716	YES
20	55		275/55R20	117V	XL	BSW	15477910000	31.9	38.8	51	11.2 (8.5)	7.0 - 9.5	2833	10	651	YES
	50		285/50R20	112V	SL	BSW	15477490000	31.2	38.2	51	11.7 (9.0)	8.0 - 10.0	2469	10	666	YES
			285/50R20	116V	XL	BSW	15494210000	31.2	36.8	51	11.7 (9.0)	8.0 - 10.0	2469	10	666	YES
			295/50R20	118V	XL	BSW	15477930000	31.6	40.7	51	12.1 (9.5)	8.0 - 10.5	2910	10	657	YES
	45		275/45R20	110V	XL	BSW	15449440000	29.7	31.5	51	10.7 (9.0)	8.5 - 10.0	2337	10	699	YES
			295/45R20	114V	XL	BSW	15477900000	30.5	38.5	51	11.7 (10.0)	9.5 - 11.0	2601	10	681	YES
22	45		305/45R22	118V	XL	BSW	15478020000	32.8	43.2	51	12.0 (10.0)	9.5 - 11.0	2910	10	633	YES
	40		305/40R22	114V	XL	BSW	15477920000	31.6	37.9	51	12.3 (11.0)	10.0 - 12.0	2601	10	657	YES
23	40		305/40R23	115V	XL	BSW	15477870000	32.6	42.1	51	12.3 (11.0)	10.0 - 12.0	2679	10	637	YES
24	35		305/35R24	112V	XL	BSW	15447940000	32.4	41.0	51	12.3 (11.0)	10.0 - 12.0	2469	10	641	YES

LIGHT TRUCK & SUV TIRES / ULTRA-HIGH PERFORMANCE / GRABBER™ UHP



GRABBER™ HTS

THIS STRONG ALL-SEASON LIGHT TRUCK, CROSSOVER AND SUV TIRE PROVIDES FUEL EFFICIENCY WITH THE PERFECT SYNERGY OF COMFORT, DURABILITY AND PERFORMANCE.

DURAGEN (ULTRA-HIGH STRENGTH STEEL BELTS, MICRO-FIBER CASING REINFORCEMENTS, AND A BROAD TIRE CONTOUR) : BORN FROM COMPETITION AND ADAPTED FOR THE HIGHWAY, THIS TECHNOLOGY PROVIDES EVEN TREADWEAR FOR LONGER MILEAGE AND CONFIDENCE IN HARSH DRIVING CONDITIONS.

COMFORT BALANCE (TREAD CUSHIONING SYSTEM AND NOISE-CAPTURING POCKETS) : A BLEND OF TECHNOLOGIES THAT PROVIDE A QUIETER, MORE COMFORTABLE RIDE WITHOUT SACRIFICING RESPONSIVENESS.

ADAPTIVE PERFORMANCE (RESPONSE GROOVES™, STABLINK BARS™ AND 3 KINDS OF SIPING) : PROMOTES ENHANCED STEERING RESPONSE AND PROVIDES RELIABLE PERFORMANCE WHEN BRAKING, ACCELERATING, AND CORNERING.

ECO RIDE (THE LATEST GENERATION TREAD COMPOUND) : IMPROVES FUEL ECONOMY DUE TO REDUCING ROLLING RESISTANCE BY 15%* AND IS DESIGNED TO MINIMIZE CO2 EMISSIONS TO SUPPORT A CLEANER ENVIRONMENT.

*COMPARED TO PREVIOUS GENERAL TIRE PRODUCTS



TO LEARN MORE ABOUT EXCLUSIVE GENERAL TIRE TECHNOLOGY INCORPORATED INTO THIS TIRE SEE PAGE 5 FOR COMPLETE DETAILS AND A SMARTPHONE LINK TO VIDEO.

TREAD: ALL-SEASON, SYMMETRIC

60000 MILE LIMITED TREADWEAR WARRANTY

Includes Metric and P-Metric sizes with speed ratings of T and below.

45000 MILE LIMITED TREADWEAR WARRANTY

Includes all Metric sizes with speed ratings of H and above and all LT Metric sizes.

45 DAY FREE TRIAL

visit www.generaltire.com for more info

UTQG: ALL PASSENGER SIZES

TREADWEAR: 640

TRACTION: A

TEMPERATURE: B



GRABBER™ HTS



RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR	
15	75	LT235/75R15	104/101Q	C	OWL	04570450000	28.9	31.7	50	9.3 (6.5)	6.0 - 7.0	1985	1820	13	719	YES	
		235/75R15	105T	SL	OWL	15485150000	28.9	31.1	44	9.3 (6.5)	6.0 - 8.0	2039	N/A	12	719	YES	
		235/75R15	109T	XL	OWL	15485570000	28.9	31.1	51	9.3 (6.5)	6.0 - 8.0	2271	N/A	12	719	YES	
		265/75R15	112S	SL	OWL	15485360000	30.6	35.7	44	10.5 (7.5)	7.0 - 9.0	2469	N/A	12	679	YES	
	70	225/70R15	100T	SL	OWL	15486010000	27.4	27.5	44	9.0 (6.5)	6.0 - 7.5	1764	N/A	12	758	YES	
		235/70R15	103T	SL	OWL	15485220000	28.0	29.8	44	9.4 (7.0)	6.5 - 8.5	1929	N/A	12	742	YES	
		255/70R15	108S	SL	OWL	15486020000	29.1	33.3	44	10.2 (7.5)	6.0 - 8.5	2205	N/A	12	714	YES	
		265/70R15	112S	SL	OWL	15485260000	29.6	34.7	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	12	702	YES	
		31X10.50R15LT	109Q	C	OWL	04570460000	30.5	37.5	50	10.5 (8.5)	7.0 - 9.0	2270	N/A	13	681	YES	
		16	85	LT235/85R16	120/116Q	E	OWL	04570400000	31.7	45.5	80	9.3 (6.5)	6.0 - 7.5	3085	2755	13	655
LT225/75R16	115/112S			E	BSW	04501200000	29.3	37.3	80	8.8 (6.0)	6.0 - 7.0	2680	2470	13	709	YES	
75	225/75R16		104S	SL	OWL	15485450000	29.3	28.9	44	8.8 (6.0)	6.0 - 7.5	1984	N/A	12	709	YES	
	235/75R16		108S	SL	OWL	15485270000	29.9	31.1	44	9.3 (6.5)	6.0 - 8.0	2205	N/A	12	695	YES	
	235/75R16		108S	SL	BSW	15485280000	29.9	30.5	44	9.3 (6.5)	6.0 - 8.0	2205	N/A	12	695	YES	
	LT245/75R16		120/116S	E	OWL	04570420000	30.5	44.1	80	9.8 (7.0)	6.5 - 7.5	3085	2755	13	681	YES	
	LT245/75R16		120/116S	E	BSW	04570820000	30.5	43.6	80	9.8 (7.0)	6.5 - 7.5	3085	2755	13	681	YES	
	245/75R16		111S	SL	BSW	15483640000	30.5	35.1	44	9.8 (7.0)	6.5 - 8.0	2403	N/A	12	681	YES	
	245/75R16		111S	SL	OWL	15485200000	30.5	34.4	44	9.8 (7.0)	6.5 - 8.0	2403	N/A	12	681	YES	
	LT265/75R16		123/120Q	E	OWL	04570430000	31.6	48.3	80	10.5 (7.5)	7.0 - 8.0	3415	3085	13	657	YES	
	265/75R16		116T	SL	OWL	15485210000	31.6	38.1	44	10.5 (7.5)	7.0 - 9.0	2756	N/A	12	657	YES	
	70		P215/70R16	99S	SL	BSW	15449050000	27.9	23.6	44	8.7 (6.5)	5.0 - 7.0	1709	N/A	11	745	YES
215/70R16			100S	SL	OWL	15486040000	27.9	25.9	44	8.7 (6.5)	5.0 - 7.0	1764	N/A	11	745	YES	
225/70R16			103S	SL	OWL	15485230000	28.4	29.0	44	9.0 (6.5)	6.0 - 7.5	1929	N/A	12	731	YES	
235/70R16			106T	SL	OWL	15485170000	29.0	31.2	44	9.4 (7.0)	6.0 - 8.0	2094	N/A	12	716	YES	
235/70R16			106T	SL	BSW	15486060000	29.0	30.6	44	9.4 (7.0)	6.0 - 8.0	2094	N/A	12	716	YES	
245/70R16			107S	SL	OWL	15485180000	29.5	33.7	44	9.8 (7.0)	6.0 - 8.0	2150	N/A	12	704	YES	
245/70R16			107S	SL	BSW	15485190000	29.5	33.1	44	9.8 (7.0)	6.0 - 8.0	2150	N/A	12	704	YES	
255/70R16			111T	SL	BSW	15485160000	30.1	33.3	44	10.2 (7.5)	6.5 - 8.5	2403	N/A	12	690	YES	
255/70R16			111S	SL	OWL	15486070000	30.1	34.0	44	10.2 (7.5)	6.5 - 8.5	2403	N/A	12	690	YES	
265/70R16		112S	SL	OWL	15485400000	30.6	37.0	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	12	679	YES		
65	265/70R16	112S	SL	BSW	15485410000	30.6	36.0	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	12	679	YES		
	275/70R16	114S	SL	OWL	15486080000	31.2	38.5	44	11.0 (8.0)	7.0 - 9.0	2601	N/A	12	666	YES		
	275/70R16	114S	SL	BSW	15486090000	31.2	37.5	44	11.0 (8.0)	7.0 - 9.0	2601	N/A	12	666	YES		
	235/65R16	103T	SL	BSW	15485530000	28.0	29.6	44	9.4 (7.0)	6.5 - 7.5	1929	N/A	12	742	YES		
	255/65R16	109S	SL	OWL	15485240000	29.1	32.7	44	10.2 (7.5)	7.0 - 9.0	2271	N/A	12	714	YES		
	255/65R16	109H	SL	BSW	15488230000	29.1	31.4	51	10.2 (7.5)	7.0 - 9.0	2271	N/A	12	714	YES		
	17	80	LT235/80R17	120/117R	E	OWL	04571040000	31.8	45.6	80	9.3 (6.5)	6.0 - 7.5	3085	2835	13	653	YES
			235/75R17	109S	SL	BSW	15485520000	30.9	32.4	44	9.3 (6.5)	6.0 - 8.0	2271	N/A	12	672	YES
		75	LT245/75R17	121/118S	E	BSW	04501840000	31.5	44.9	80	9.7 (7.0)	6.0 - 7.5	3195	2910	13	659	YES
			LT245/75R17	121/118S	E	OWL	04571060000	31.5	46.8	80	9.7 (7.0)	6.0 - 7.5	3195	2910	12	659	YES

N/A = Not Applicable

Continued next page

LIGHT TRUCK & SUV TIRES / HIGHWAY TERRAIN / GRABBER™ HTS

GRABBER™ HTS

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
17	70	235/70R17	111T	XL	OWL	15485460000	30.0	31.7	51	9.4 (7.0)	6.0 - 8.0	2403	N/A	12	692	YES
		LT245/70R17	119/116S	E	OWL	04571080000	30.5	45.4	80	9.8 (7.0)	6.5 - 8.0	3000	2755	13	681	YES
		P245/70R17	108S	SL	BSW	15448420000	30.5	30.8	44	9.8 (7.0)	6.5 - 8.0	2205	N/A	11	681	YES
		245/70R17	110S	SL	OWL	15448720000	30.5	32.0	44	9.8 (7.0)	6.5 - 8.0	2205	N/A	11	681	YES
		P245/70R17	108T	SL	BSW	15449490000	30.5	31.5	44	9.8 (7.0)	6.5 - 8.0	2205	N/A	11	681	YES
		LT265/70R17	121/118S	E	OWL	04570470000	31.6	46.9	80	10.7 (8.0)	7.0 - 9.0	3195	2910	13	657	YES
		P265/70R17	113S	SL	BSW	15485420000	31.6	36.9	44	10.7 (8.0)	7.0 - 9.0	2535	N/A	12	657	YES
		P265/70R17	113S	SL	OWL	15485430000	31.6	37.8	44	10.7 (8.0)	7.0 - 9.0	2535	N/A	12	657	YES
		LT285/70R17	121/118Q	D	OWL	04571100000	33.7	51.6	65	11.5 (8.5)	7.5 - 9.5	3195	2910	13	616	YES
	LT315/70R17	121/118S	D	BSW	04571090000	34.4	56.8	65	12.7 (9.5)	8.5 - 10.0	3195	2910	13	604	YES	
	65	225/65R17	102T	SL	BSW	15483160000	28.5	27.8	44	9.0 (6.5)	6.0 - 8.0	1874	N/A	12	729	YES
		235/65R17	108H	XL	BSW	15485310000	29.0	29.1	51	9.4 (7.0)	6.5 - 8.5	2205	N/A	12	716	YES
		235/65R17	108T	XL	OWL	15485320000	29.0	29.8	51	9.4 (7.0)	6.5 - 8.5	2205	N/A	12	716	YES
		245/65R17	111T	XL	OWL	15483570000	29.5	32.2	51	9.8 (7.0)	7.0 - 8.5	2403	N/A	12	704	YES
		255/65R17	110S	SL	BSW	15448730000	30.1	36.0	44	10.2 (7.5)	7.0 - 9.0	2337	N/A	12	690	YES
		265/65R17	112T	SL	OWL	15485490000	30.6	35.8	44	10.7 (8.0)	7.5 - 9.5	2469	N/A	12	679	YES
	60	275/60R17	110S	SL	OWL	15485300000	30.0	37.1	44	11.0 (8.0)	7.5 - 9.5	2337	N/A	12	692	YES
55	275/55R17	109V	SL	BSW	15488250000	28.9	33.2	51	11.2 (8.5)	7.5 - 9.5	2271	N/A	10	719	YES	
18	70	255/70R18	113T	SL	OWL	15483170000	32.1	36.8	44	10.2 (7.5)	6.5 - 8.5	2535	N/A	12	647	YES
		265/70R18	116S	SL	OWL	15485500000	32.6	38.5	44	10.7 (8.0)	7.0 - 9.0	2756	N/A	12	637	YES
		LT275/70R18	125/122S	E	OWL	04571130000	33.2	52.1	80	10.9 (8.0)	7.0 - 9.0	3640	3305	13	626	YES
	65	235/65R18	106S	SL	OWL	15483180000	30.0	31.3	44	9.4 (7.0)	6.5 - 8.5	2095	N/A	12	692	YES
		LT275/65R18	123/120S	E	OWL	04571110000	32.1	51.9	80	10.9 (8.0)	7.0 - 8.5	3415	3085	13	647	YES
	60	265/60R18	110T	SL	OWL	15488260000	30.5	36.4	44	10.7 (8.0)	7.5 - 9.5	2337	N/A	12	681	YES
		275/60R18	113H	SL	BSW	15488270000	31.0	39.9	51	11.0 (8.0)	7.5 - 9.5	2535	N/A	12	670	YES
55	255/55R18	109H	XL	BSW	15485350000	29.0	35.0	51	10.4 (8.0)	7.0 - 9.0	2271	N/A	12	716	YES	
20	60	LT275/65R20	126/123S	E	OWL	04571120000	34.1	57.1	80	11.0 (8.0)	7.5 - 9.5	3750	3415	13	609	YES
		275/60R20	119S	XL	BSW	15485380000	33.0	40.6	51	11.0 (8.0)	7.5 - 9.5	2998	N/A	12	630	YES
		275/60R20	119S	XL	OWL	15485390000	33.0	40.8	51	11.0 (8.0)	7.5 - 9.5	2998	N/A	12	630	YES
	55	275/55R20	117S	XL	BSW	15485370000	31.9	38.6	51	11.2 (8.5)	7.0 - 9.5	2833	N/A	12	651	YES

LT New size for 2012 Second Edition

N/A = Not Applicable



GRABBER™ AT²

THIS TOUGH, ALL-TERRAIN TIRE IS DESIGNED WITH AN AGGRESSIVE, SELF-CLEANING TREAD PATTERN THAT PROVIDES OFF-ROAD TRACTION, DURABILITY AND IMPRESSIVE PAVED ROAD PERFORMANCE.

5-ROW TREAD PATTERN WITH MULTIPLE TRACTION EDGES : INNOVATIVE TREAD DESIGN PROMOTES UNCOMPROMISING ON- AND OFF-ROAD TRACTION.

DOUBLE V-SHAPED TREAD PATTERN : DESIGNED TO INCREASE TREAD LIFE AND OFF-ROAD DURABILITY.

HIGHLY-ENGINEERED ACOUSTIC TREAD PATTERN : ALLOWS THE AGGRESSIVE TREAD PATTERN TO PROVIDE A QUIET, COMFORTABLE RIDE DURING HIGHWAY DRIVING.

*SNOWFLAKE APPROVED AND STUDDABLE DESIGN : MEETS THE SEVERE SNOW SERVICE REQUIREMENTS OF THE RMA AND RAC.



TO LEARN MORE ABOUT EXCLUSIVE GENERAL TIRE TECHNOLOGY INCORPORATED INTO THIS TIRE SEE PAGE 5 FOR COMPLETE DETAILS AND A SMARTPHONE LINK TO VIDEO.

TREAD: ALL-TERRAIN, SYMMETRIC

60000 MILE LIMITED TREADWEAR WARRANTY
Includes metric sizes with speed ratings of T and below.

30 DAY FREE TRIAL
visit www.generaltire.com for more info

UTQG: ALL PASSENGER SIZES

TREADWEAR:	640
TRACTION:	A
TEMPERATURE:	B

* SELECT SIZES MEET THE SEVERE SNOW SERVICE REQUIREMENTS OF THE RUBBER MANUFACTURERS ASSOCIATIONS (RMA) AND THE RUBBER ASSOCIATION OF CANADA (RAC). STUDDABLE



GRABBER™ AT²



RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
14		27X8.50R14LT	95Q	C	OWL	05684400000	26.5	28.9	50	8.6 (7.0)	6.0 - 7.5	1520	N/A	16	784	NO
75		205/75R15	97T	SL	OWL	15463680000	27.1	23.9	44	8.0 (5.5)	5.5 - 7.0	1609	N/A	13	767	NO
		215/75R15*	100S	SL	OWL	15463720000	27.7	28.1	44	8.5 (6.0)	5.5 - 7.0	1764	N/A	13	750	NO
		225/75R15	102S	SL	OWL	15463730000	28.3	30.3	44	8.8 (6.0)	6.0 - 7.5	1874	N/A	16	734	NO
		LT235/75R15	104/101S	C	OWL	05684060000	28.9	33.6	50	9.3 (6.5)	6.0 - 7.0	1985	1820	16	719	YES
70		225/70R15	100S	SL	OWL	15474600000	27.4	30.7	44	9.0 (6.5)	6.0 - 7.5	1764	N/A	16	758	YES
		255/70R15*	108S	SL	BSW	15483390000	29.1	39.4	44	10.2 (7.5)	6.0 - 8.5	2205	N/A	16	714	YES
		265/70R15	112S	SL	OWL	15463780000	29.6	39.9	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	16	702	YES
33X12.50R15LT		33X12.50R15LT	108Q	C	OWL	05684050000	32.8	50.2	35	12.5 (10.0)	8.5 - 11.0	2205	N/A	16	633	YES
		35X12.50R15LT*	113Q	C	OWL	04320070000	34.8	64.4	35	12.5 (10.0)	8.5 - 11.0	2535	N/A	16	597	YES
		31X10.50R15LT	109S	C	OWL	05684040000	30.8	39.4	50	10.5 (8.5)	7.0 - 9.0	2270	N/A	16	674	YES
		30X9.50R15LT	104S	C	OWL	05684030000	29.7	36.0	50	9.5 (7.5)	6.5 - 8.5	1985	N/A	16	699	YES
85		LT235/85R16	120/116S	E	OWL	05684070000	31.7	48.5	80	9.3 (6.5)	6.0 - 7.5	3085	2755	16	655	YES
		225/75R16*	108S	XL	OWL	15463740000	29.3	36.1	51	8.8 (6.0)	6.0 - 7.5	2205	N/A	16	709	YES
		LT245/75R16	120/116S	E	OWL	05684080000	30.5	46.0	80	9.8 (7.0)	6.5 - 7.5	3085	2755	16	681	YES
		LT265/75R16	123/120Q	E	OWL	05684090000	31.6	51.1	80	10.5 (7.5)	7.0 - 8.0	3415	3085	16	657	YES
		LT285/75R16	122/119Q	D	OWL	05684100000	32.8	56.4	65	11.3 (8.0)	7.5 - 9.0	3305	3000	16	633	YES
		LT295/75R16	123/120Q	D	OWL	05684110000	33.4	56.5	65	11.6 (8.0)	7.5 - 9.5	3415	3085	16	622	YES
75		LT315/75R16	121Q	D	OWL	05684120000	34.6	62.9	50	12.3 (8.5)	8.0 - 10.0	3195	N/A	16	600	YES
		215/70R16*	100T	SL	BSW	15463710000	27.9	28.6	44	8.7 (6.5)	5.0 - 7.0	1764	N/A	14	745	YES
		235/70R16*	106T	SL	OWL	15449570000	29.0	31.8	44	9.4 (7.0)	6.0 - 8.0	2094	N/A	13	716	YES
		245/70R16*	107T	SL	OWL	15463760000	29.5	36.1	44	9.8 (7.0)	6.5 - 8.0	2150	N/A	16	704	YES
		255/70R16	111S	SL	OWL	15474590000	30.1	38.9	44	10.2 (7.5)	6.5 - 8.5	2403	N/A	16	690	YES
		265/70R16	112T	SL	OWL	15483090000	30.6	40.8	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	16	679	YES
70		LT305/70R16	118/115Q	D	OWL	05684190000	32.8	57.1	50	12.2 (9.0)	8.0 - 9.5	2910	2680	16	633	YES
		215/65R16*	98T	SL	BSW	15463700000	27.0	27.9	44	8.7 (6.5)	6.0 - 7.5	1654	N/A	14	769	YES
		255/65R16*	109T	SL	OWL	15463770000	29.1	37.0	44	10.2 (7.5)	7.0 - 9.0	2271	N/A	16	714	YES
80		LT235/80R17	120/117Q	E	OWL	04563390000	31.8	45.1	80	9.3 (6.5)	6.0 - 7.5	3085	2835	16	653	NO
		245/70R17	110S	SL	OWL	15447730000	30.5	38.6	44	9.8 (7.0)	6.5 - 8.0	2337	N/A	16	681	NO
		255/70R17	112S	SL	BSW	15447660000	31.1	38.8	44	10.2 (7.5)	6.5 - 8.5	2469	N/A	16	668	NO
		LT265/70R17	121/118Q	E	OWL	04564990000	31.6	48.5	80	10.7 (8.0)	7.0 - 9.0	3195	2910	16	657	NO
		265/70R17*	115S	SL	OWL	04569480000	31.6	42.0	44	10.7 (8.0)	7.5 - 9.5	2679	N/A	16	657	YES
		255/65R17	110S	SL	OWL	15447710000	30.1	39.0	44	10.2 (7.5)	7.0 - 9.0	2337	N/A	16	690	NO
65		265/65R17	112S	SL	OWL	15447810000	30.6	39.2	44	10.7 (8.0)	7.5 - 9.5	2469	N/A	16	679	NO
		265/65R17	112T	SL	BSW	15449010000	30.6	40.8	44	10.7 (8.0)	7.5 - 9.5	2469	N/A	16	679	YES
		33X12.50R17LT*	105Q	C	OWL	04568640000	32.8	58.7	50	12.5 (10.0)	8.5 - 11.0	2040	N/A	16	633	YES
	35X12.50R17LT*	119Q	D	OWL	04568650000	34.8	63.9	65	12.5 (10.0)	8.5 - 11.0	3000	N/A	16	597	YES	
70		265/70R18	116S	SL	OWL	15447740000	32.6	42.8	44	10.7 (8.0)	7.0 - 9.0	2756	N/A	16	637	NO
		LT275/70R18	125/122Q	E	OWL	04566550000	33.2	54.3	80	10.9 (8.0)	7.0 - 9.0	3640	3305	16	626	NO
65		275/65R18	116S	SL	BSW	04501220000	32.1	42.5	44	10.9 (8.0)	7.5 - 9.5	2756	N/A	16	647	YES

Standard Stud Size: TSMI #13 Gold
* Indicates sizes does not carry snowflake designation
N/A = Not Applicable

Continued next page

LIGHT TRUCK & SUV TIRES / ALL-TERRAIN / GRABBER™ AT²

GRABBER™ AT²

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
18	65	LT275/65R18	123/120Q	E	OWL	04565950000	32.1	52.1	80	10.9 (8.0)	7.0 - 8.5	3415	3085	16	647	NO	
		255/60R18*	112H	XL	BSW	15484070000	30.0	38.0	51	10.2 (7.5)	7.0 - 9.0	2469	N/A	13	692	YES	
	60	LT285/60R18	122/119Q	E	BSW	04566890000	31.5	53.9	80	11.5 (8.5)	8.0 - 10.0	3305	3000	16	659	NO	
		255/55R18*	109H	XL	BSW	15477940000	29.0	36.8	51	10.4 (8.0)	7.0 - 9.0	2271	N/A	13	716	YES	
	55	33X12.50R18LT*	118Q	E	BSW	04568660000	32.8	61.1	80	12.5 (10.0)	8.5 - 11.0	2910	N/A	16	633	YES	
		35X12.50R18LT*	118Q	D	BSW	04568670000	34.8	63.5	65	12.5 (10.0)	8.5 - 11.0	2910	N/A	16	597	YES	
20	50	305/50R20	120T	XL	BSW	15478240000	32.0	50.4	51	12.4 (9.5)	8.5 - 11.0	3086	N/A	16	649	YES	
		33X12.50R20LT*	114Q	E	BSW	04568680000	32.8	63.3	80	12.5 (10.0)	8.5 - 11.0	2600	N/A	16	633	YES	
			35X12.50R20LT*	121Q	E	BSW	04568690000	34.8	66.6	80	12.5 (10.0)	8.5 - 11.0	3195	N/A	16	597	YES

Standard Stud Size: TSMI #13 Gold
 * Indicates sizes does not carry snowflake designation
 N/A = Not Applicable



GRABBER™

BORN FROM COMPETITION, THIS EXTREME TRACTION TIRE PROVIDES EXCEPTIONAL OFF-ROAD GRIP AND DURABILITY, BALANCED WITH ON-ROAD DRIVABILITY.

3-PLY CONSTRUCTION : RACE PROVEN DURABILITY AND PUNCTURE RESISTANCE PROVIDES DRIVING CONFIDENCE UNDER THE WORLD'S MOST EXTREME CONDITIONS.

PATENTED STRAKE AND CHAMFER TREAD PATTERN : DELIVERS DECEPTIVELY HIGH LEVELS OF TRACTION IN BOTH MUD AND SILT .

REACTIVE CONTOUR TECHNOLOGY : DELIVERS EVEN TREADWEAR THROUGHOUT THE LIFE OF THE TIRE.

ACOUSTIC MODULATION SOUND TECHNOLOGY (AMST) : SOUND WAVE SUPPRESSION THAT WORKS TO REDUCE ROAD NOISE.

RACE INSPIRED SIDEWALL DESIGN : MULTI-ANGLED SIDEWALL PROTECTORS HELP PREVENT PUNCTURES.



TO LEARN MORE ABOUT EXCLUSIVE GENERAL TIRE TECHNOLOGY INCORPORATED INTO THIS TIRE SEE PAGE 5 FOR COMPLETE DETAILS AND A SMARTPHONE LINK TO VIDEO.



TREADS EXTREMETRACTION, SYMMETRIC

30 DAY FREE TRIAL
visit www.generaltire.com for more info



GRABBER™



RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
15	50	31X10.50R15LT	109Q	C	SRL	04568150000	31	55.0	50	10.5 (8.5)	7.0 - 9.0	2270	N/A	18	670	yes
		33X10.50R15LT	114Q	C	SRL	04501800000	33	62.0	50	10.5 (8.5)	7.0 - 9.0	2600	N/A	18	630	yes
		33X12.50R15LT	108Q	C	SRL	04568160000	33	65.7	35	12.5 (10.0)	8.5 - 11.0	2205	N/A	18	630	yes
		35X12.50R15LT	113Q	C	SRL	04568200000	35	71.4	35	12.5 (10.0)	8.5 - 11.0	2535	N/A	18	594	yes
16	75	LT265/75R16	112/109Q	C	SRL	04500930000	31.6	49.5	50	10.5 (7.50)	7.0 - 8.0	2470	2270	18	657	yes
		LT285/75R16	126Q	E	SRL	04568370000	32.8	66.6	80	11.3 (8.0)	7.5 - 9.0	3750	N/A	18	633	yes
		LT315/75R16	121Q	D	SRL	04568390000	34.6	74.9	50	12.3 (8.5)	8.0 - 11.0	3195	N/A	18	600	yes
17	50	33X12.50R17LT	105Q	C	SRL	04568170000	33	71.1	35	12.5 (10.0)	8.5 - 11.0	2040	N/A	18	630	yes
		35X12.50R17LT	121Q	E	SRL	04568210000	35	76.6	65	12.5 (10.0)	8.5 - 11.0	3195	N/A	18	594	yes
18	70	LT275/70R18	125/122Q	E	SRL	04568350000	33.2	66.5	80	10.8 (8.0)	7.0 - 8.5	3640	3305	18	626	yes
		33X12.50R18LT	118Q	E	BSW	04568180000	33	74.2	65	12.5 (10.0)	8.5 - 11.0	2910	N/A	18	630	yes
	50	35X12.50R18LT	123Q	E	SRL	04500630000	35	77.8	65	12.5 (10.0)	8.5 - 11.0	3415	N/A	18	594	yes
		35X12.50R18LT	123Q	E	BSW	04568220000	35	77.7	65	12.5 (10.0)	8.5 - 11.0	3415	N/A	18	594	yes
20	50	LT315/50R20	112/109Q	D	BSW	04568190000	32.4	73.8	50	12.9 (10.0)	8.5 - 11.0	2470	2270	18	641	yes
		35X12.50R20LT	121Q	E	SRL	04500640000	35	81.4	65	12.5 (10.0)	8.5 - 11.0	3195	N/A	18	594	yes
		35X12.50R20LT	121Q	E	BSW	04568230000	35	81.2	65	12.5 (10.0)	8.5 - 11.0	3195	N/A	18	594	yes

SRL = Smooth Red Letter

N/A = Not Applicable

LIGHT TRUCK & SUV TIRES / EXTREME TERRAIN / GRABBER™

ALTIMAX™ ARCTIC

UNIQUE GROOVES AND SIPES COMBINE WITH A MODERN COMPOUND TO OFFER OUTSTANDING PERFORMANCE IN LOW TEMPERATURES.

MULTI-ANGLE SIPE SYSTEM : 270 DEGREES OF SIPES WITH BITING EDGES THAT MAXIMIZE SNOW, ICE AND WET TRACTION IN ALL DIRECTIONS.

DIRECTIONAL TREAD PATTERN WITH CENTER STABILITY RIB : PROVIDES ACTIVE WATER EVACUATION WHILE THE SOLID CENTER RIB PROVIDES STRAIGHT-LINE STABILITY .

REACTIVE CONTOUR TECHNOLOGY (RCT) : CONTOUR REACTS TO DIFFERENT ROAD CONDITIONS TO MAINTAIN ENHANCED CONTACT WITH ROAD SURFACE THROUGHOUT THE LIFE OF THE TIRE.

ALL-WEATHER DUAL TREAD COMPOUND : A MIXTURE OF NATURAL RUBBER AND SILICA RUBBER COMPOUND MAINTAINS COLD-WEATHER FLEXIBILITY AND PROVIDES EXCELLENT WET TRACTION AND LONG EVEN TREADWEAR.



TREADS: WINTER STUDDABLE, DIRECTIONAL

45 DAY FREE TRIAL
visit www.generaltire.com for more info

MEETS THE SEVERE SNOW SERVICE REQUIREMENTS OF THE RUBBER MANUFACTURERS ASSOCIATIONS (RMA) AND THE RUBBER ASSOCIATION OF CANADA (RAC). STUDDABLE



ALTIMAX™ ARCTIC



	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR
13	70		175/70R13	82Q	SL	BSW	15486000000	22.6	14.5	44	7.0 (5.0)	4.5 - 6.0	1047	N/A	12	919	NO
	70		185/70R14	88Q	SL	BSW	15486100000	24.2	16.9	44	7.4 (5.5)	4.5 - 6.0	1235	N/A	12	858	NO
14	65		175/65R14	82Q	SL	BSW	15486110000	23.0	14.5	44	7.0 (5.0)	5.0 - 6.0	1047	N/A	12	903	NO
	65		185/65R14	86Q	SL	BSW	15486120000	23.5	15.8	44	7.4 (5.5)	5.0 - 6.5	1168	N/A	12	884	NO
	60		185/60R14	82Q	SL	BSW	15489030000	22.7	16.4	44	7.4 (5.5)	5.0 - 6.5	1047	N/A	12	915	NO
15	70		205/70R15	96Q	SL	BSW	15486200000	26.3	21.4	44	8.2 (6.0)	5.0 - 7.0	1565	N/A	12	790	NO
	70		215/70R15	98Q	SL	BSW	15486300000	26.9	26.0	44	8.7 (6.5)	5.5 - 7.0	1654	N/A	12	772	NO
	70		225/70R15	100Q	SL	BSW	15455980000	27.4	27.1	44	9.0 (6.5)	6.0 - 7.5	1764	N/A	12	758	NO
	65		185/65R15	88Q	SL	BSW	15486130000	24.5	17.1	44	7.4 (5.5)	5.0 - 6.5	1235	N/A	12	848	NO
	65		195/65R15	91Q	SL	BSW	15486140000	25.0	19.7	44	7.9 (6.0)	5.5 - 7.0	1356	N/A	12	831	NO
	65		205/65R15	94Q	SL	BSW	15486150000	25.5	20.4	44	8.2 (6.0)	5.5 - 7.5	1477	N/A	12	815	NO
	65		215/65R15	96Q	SL	BSW	15454580000	26.0	23.1	44	8.7 (6.5)	6.0 - 7.5	1565	N/A	12	799	NO
	60		185/60R15	84Q	SL	BSW	15486160000	23.7	16.7	44	7.4 (5.5)	5.0 - 6.5	1102	N/A	12	877	NO
	60		195/60R15	88Q	SL	BSW	15486170000	24.2	17.7	44	8.0 (6.0)	5.0 - 7.0	1235	N/A	12	858	NO
	60		205/60R15	91Q	SL	BSW	15486220000	24.7	20.2	44	8.2 (6.0)	5.5 - 7.5	1356	N/A	12	841	NO
	60		215/60R15	94Q	SL	BSW	15453470000	25.2	21.7	44	8.7 (6.5)	6.0 - 7.5	1477	N/A	12	824	NO
	55		195/55R15	85Q	SL	BSW	15486180000	23.4	17.6	44	7.9 (6.0)	5.5 - 7.0	1135	N/A	12	888	NO
16	85		LT235/85R16	120/116Q	E	BSW	04568510000	31.7	48.0	80	9.2 (6.5)	6.5 - 7.5	3085	2755	16	655	NO
	75		LT225/75R16	115/112Q	E	BSW	04568490000	29.3	42.3	80	8.8 (6.0)	6.0 - 7.0	2680	2470	16	709	NO
	75		235/75R16	108Q	SL	BSW	15456980000	29.9	31.3	44	9.3 (6.5)	6.0 - 8.0	2205	N/A	12	695	NO
	75		LT245/75R16	120/116Q	E	BSW	04568530000	30.5	46.0	80	9.8 (7.0)	6.5 - 7.5	3085	2755	16	681	NO
	75		245/75R16	111Q	SL	BSW	15457730000	30.5	33.5	44	9.8 (7.0)	6.5 - 8.0	2403	N/A	12	681	NO
	75		LT265/75R16	123/120Q	E	BSW	04568550000	31.6	49.5	80	10.5 (7.5)	7.0 - 8.0	3415	3085	16	657	NO
	75		265/75R16	116Q	SL	BSW	15458960000	31.6	38.5	44	10.5 (7.5)	7.0 - 9.0	2756	N/A	12	657	NO
	70		215/70R16	100Q	SL	BSW	15531580000	27.9	27.7	44	8.7 (6.5)	5.5 - 7.0	1764	N/A	12	745	NO
	70		225/70R16	103Q	SL	BSW	15486190000	28.4	29.7	44	9.0 (6.5)	6.0 - 7.5	1929	N/A	12	731	NO
	70		235/70R16	106Q	SL	BSW	15531030000	29.0	30.1	44	9.4 (7.0)	6.0 - 8.0	2094	N/A	12	716	NO
	70		245/70R16	107Q	SL	BSW	15489020000	29.5	31.6	44	9.8 (7.0)	6.0 - 8.0	2150	N/A	12	704	NO
	70		255/70R16	111Q	SL	BSW	15457960000	30.1	33.6	44	10.2 (7.5)	6.5 - 8.5	2403	N/A	12	690	NO
	70		265/70R16	112Q	SL	BSW	15457990000	30.6	35.6	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	12	679	NO
	65		215/65R16	98Q	SL	BSW	15486210000	27.0	23.4	44	8.7 (6.5)	6.0 - 7.5	1654	N/A	12	769	NO
	60		205/60R16	92Q	SL	BSW	15486230000	25.7	21.2	44	8.2 (6.0)	5.5 - 7.5	1389	N/A	12	808	NO
	60		215/60R16	95Q	SL	BSW	15486240000	26.2	23.4	44	8.7 (6.5)	6.0 - 7.5	1521	N/A	12	793	NO
	60		225/60R16	98Q	SL	BSW	15486250000	26.6	23.3	44	9.0 (6.5)	6.0 - 8.0	1654	N/A	12	781	NO
	60		235/60R16	100Q	SL	BSW	15486290000	27.1	24.2	44	9.4 (7.0)	6.5 - 8.5	1764	N/A	12	767	NO
55		205/55R16	91Q	SL	BSW	15486260000	24.9	19.9	44	8.4 (6.5)	5.5 - 7.5	1356	N/A	12	834	NO	
55		215/55R16	93Q	SL	BSW	15486270000	25.3	21.9	44	8.9 (7.0)	6.0 - 7.5	1433	N/A	12	821	NO	
55		225/55R16	95Q	SL	BSW	15486280000	25.7	22.6	44	9.2 (7.0)	6.0 - 8.0	1521	N/A	12	808	NO	
17	80		LT235/80R17	120/117Q	E	BSW	04568500000	31.8	48.4	80	9.3 (6.5)	6.0 - 7.5	3085	2835	16	653	NO
	70		LT245/70R17	119/116Q	E	BSW	04568520000	30.5	48.4	80	9.8 (7.0)	6.5 - 8.0	3000	2755	16	681	NO

LT Standard Stud Size: TSMI #13 (12mm)
All Other Sizes: TSMI #12 (11mm)
N/A = Not Applicable

Continued next page

WINTER TIRES / ALTIMAX™ ARCTIC

ALTIMAX™ ARCTIC

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	RIM PROTECTOR	
17	70	245/70R17	110Q	SL	BSW	15457460000	30.5	34.0	44	9.8 (7.0)	6.5 - 8.0	2337	N/A	12	681	NO	
		LT265/70R17	121/118Q	E	BSW	04568540000	31.6	51.8	80	10.7 (8.0)	7.0 - 9.0	3195	2910	16	657	NO	
		265/70R17	115Q	SL	BSW	15458120000	31.6	36.7	44	10.7 (8.0)	7.0 - 9.0	2679	N/A	12	657	NO	
		LT285/70R17	121/118Q	D	BSW	04568560000	32.7	55.4	80	11.5 (8.5)	7.0 - 9.0	3195	2910	16	635	NO	
	65	215/65R17	99Q	SL	BSW	15489010000	28.0	26.2	44	8.7 (6.5)	6.0 - 7.5	1709	N/A	12	742	NO	
		225/65R17	102Q	SL	BSW	15488990000	28.5	29.2	44	9.0 (6.5)	6.0 - 8.0	1874	N/A	12	729	NO	
		235/65R17	108Q	XL	BSW	15486310000	29.0	32.7	51	9.4 (7.0)	6.5 - 8.5	2205	N/A	12	716	YES	
		245/65R17	107Q	SL	BSW	15456990000	29.5	33.0	44	9.8 (7.0)	7.0 - 8.5	2150	N/A	12	704	NO	
		265/65R17	112Q	SL	BSW	15457980000	30.6	36.4	44	10.7 (8.0)	7.5 - 9.5	2469	N/A	12	679	NO	
	60	215/60R17	96Q	SL	BSW	15453480000	27.2	23.9	44	9.3 (6.5)	6.0 - 7.5	1565	N/A	12	764	NO	
		225/60R17	99Q	SL	BSW	15489000000	27.6	25.4	44	9.0 (6.5)	6.0 - 8.0	1709	N/A	12	753	NO	
	55	215/55R17	94Q	SL	BSW	15452050000	26.3	23.2	44	8.9 (7.0)	6.0 - 7.5	1477	N/A	12	790	NO	
		225/55R17	97Q	SL	BSW	15455000000	26.7	24.9	44	9.2 (7.0)	6.0 - 8.0	1609	N/A	12	778	NO	
	50	235/55R17	99Q	SL	BSW	15455990000	27.2	29.9	44	9.6 (7.5)	6.5 - 8.6	1709	N/A	12	764	NO	
		205/50R17	93Q	XL	BSW	15486320000	25.1	22.2	51	8.4 (6.5)	5.5 - 7.5	1433	N/A	12	828	YES	
	45	215/50R17	91Q	SL	BSW	15451570000	25.5	22.4	44	8.9 (7.0)	6.0 - 7.5	1356	N/A	12	815	YES	
		215/45R17	87Q	SL	BSW	15451480000	24.6	20.8	44	8.5 (7.0)	7.0 - 8.0	1202	N/A	12	844	YES	
		225/45R17	91Q	SL	BSW	15486330000	25.0	21.9	44	8.9 (7.5)	7.0 - 8.5	1356	N/A	12	831	YES	
			235/45R17	94Q	SL	BSW	15486340000	25.3	24.0	44	9.3 (8.0)	7.5 - 9.0	1477	N/A	12	821	YES

LT Standard Stud Size: TSMI #13 (12mm)
 All Other Size: TSMI #12 (11mm)
 N/A = Not Applicable



ORIGINAL EQUIPMENT PRODUCT LINES



AMERITRAC™



AMERITRAC™ TR



GRABBER™ HTS



GRABBER™ AW



GRABBER™ TR

OE	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (IN)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (IN) (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (32NDS)	REVS PER MILE	UTQG
----	--------------	--------	------	--------------------	------------	----------	----------------	--------------------	------------------	-------------------------------	--	--------------------------	----------------	---------------------	---------------------	---------------	------

AMERITRAC™

GM	16	85	LT215/85R16	115/112S	E	BSW	04501160000	30.4	37.1	80	8.5 (6.0)	5.5 - 7.0	2680	2470	13	683	NONE
	70		P255/70R16	109H	SL	BSW	15480400000	30.1	35.3	44	10.2 (7.5)	6.5 - 8.5	2271		11	690	420 B B
DODGE	17	80	LT235/80R17	120/117R	E	BSW	04501890000	31.8	47.4	80	9.3 (6.5)	6.0 - 7.5	3085	2835	14	653	NONE
CHEV/ GMC		70	P245/70R17	108S	SL	BSW	15448380000	30.5	28.4	44	9.8 (7.0)	6.5 - 8.0	2205		10	681	420 B B
			P245/70R17	108H	SL	BSW	15449020000	30.5	31.3	44	9.8 (7.0)	6.5 - 8.0	2205		10	681	420 B B

AMERITRAC™ TR

DODGE	17	80	LT235/80R17	120/117R	E	OWL	04501870000	31.8	45.1	80	9.3 (6.5)	6.0 - 7.5	3085	2835	16	653	NONE
			LT235/80R17	120/117R	E	BSW	04501880000	31.8	47.8	80	9.3 (6.5)	6.0 - 7.5	3085	2835	16	653	NONE
FORD		70	P255/70R17	110S	SL	OWL	15448240000	31.1	36.4	44	10.2 (7.5)	6.5 - 8.5	2337		14	668	500 A B
GM			P265/70R17	113H	SL	BSW	15482850000	31.6	37.0	44	10.7 (8.0)	7.0 - 9.0	2535		13	657	500 A A

GRABBER™ AW

NISSAN	15	75	P235/75R15	105S	SL	BSW	15480030000	28.9	27.8	44	9.3 (6.5)	6.0 - 8.0	2039		12	719	420 B B
NISSAN	16	75	P245/75R16	109S	SL	BSW	15473830000	30.5	30.3	44	9.8 (7.0)	6.5 - 8.0	2271		11	681	420 B B
		70	P265/70R16	111S	SL	BSW	15473840000	30.6	33.2	44	10.7 (8.0)	7.0 - 9.0	2403		12	679	420 B B
NISSAN	17	65	P265/65R17	110S	SL	BSW	15473850000	30.6	32.6	44	10.7 (8.0)	7.5 - 9.5	2337		12	679	420 B B

GRABBER™ HTS

NISSAN	15	70	225/70R15	100T	SL	OWL	15486010000	27.4	27.5	44	9.0 (6.5)	6.0 - 7.5	800	1764	12	758	640 A B
GM	16	75	LT225/75R16	115/112S	E	BSW	04501200000	29.3	37.3	80	8.8 (6.0)	6.0 - 7.0	2680	2470	13	709	NONE
		70	P215/70R16	99S	SL	BSW	15449050000	27.9	23.6	44	8.7 (6.5)	5.0 - 7.0	1709		11	745	640 A B
FORD	17	75	LT245/75R17	121/118S	E	BSW	04501840000	31.5	44.9	80	9.7 (7.0)	6.0 - 7.5	3195	2910		659	NONE
GM		70	P245/70R17	108S	SL	BSW	15448420000	30.5	30.8	44	9.8 (7.0)	6.5 - 8.0	2205		11	681	640 A B
			P245/70R17	108T	SL	BSW	15449490000	30.5	31.5	44	9.8 (7.0)	6.5 - 8.0	2205		11	681	640 A B
AM GENERAL		65	235/65R17	108T	XL	OWL	15485320000	29.0	29.8	51	9.4 (7.0)	6.5 - 8.5	1000	2205	12	716	640 A B

ORIGINAL EQUIPMENT REFERENCE GUIDE

ARTICLE NUMBER	DISCONTINUED	SIZE & SPEED/LOAD INDEX	TIRE NAME	SIDEWALL	***ALTERNATIVE FITMENT	***ALTERNATIVE TIRE LINE	YEAR SELECTED AS OE
----------------	--------------	-------------------------	-----------	----------	------------------------	--------------------------	---------------------

AM GENERAL AV-1

15485310000		235/65R17 108H XL	Grabber HTS	BSW							13
15485320000		235/65R17 108T XL	Grabber HTS	BSW							12

CHEVROLET - COLORADO

15448880000	X	P215/70R16 99S SL	Ameri*GS60	BSW	15449050000	Grabber HTS	09					
15449050000		P215/70R16 99S SL	Grabber HTS	BSW			09	10	11	12		

CHEVROLET - EXPRESS

04501160000		LT215/85R16 115/112S E	AmeriTrac	BSW				10	11			
04568620000	X	LT215/85R16 115/112S E	AmeriTrac	BSW	no replacement		09	10				
04501200000		LT225/75R16 115/112S E	Grabber HTS	BSW					11	12	13	
15448380000		P245/70R17 108S SL	AmeriTrac	BSW			09	10	11	12	13	
15448430000	X	P245/70R17 108S SL	AmeriTrac	OWL	15448720000	Grabber HTS	09					

CHEVROLET - SILVERADO

04569100000		LT225/75R17 116/113Q E	Grabber AW	BSW			09	10				
04569260000		LT225/75R17 116/113Q E	Grabber TR	BSW			09	10				
15448410000	X	P245/70R17 108S SL	AmeriTrac	BSW	15449490000	Grabber HTS	09	10				
15484700000	X	P245/70R17 108S SL	AmeriTrac	BSW	15449490000	AmeriTrac		10				
15449490000		P245/70R17 108T SL	Grabber HTS	BSW			09	10	11	12	13	
15449020000		P245/70R17 108H SL	AmeriTrac	BSW				10	11	12	13	
15476370000	X	P245/70R17 108H SL	AmeriTrac	BSW	15449020000	AmeriTrac	09	10				
15490430000		P255/70R17 CONT	Grabber HTS	BSW								13
15482850000		P265/70R17 113H SL	AmeriTrac TR	BSW			09	10	11	12	13	

CHEVROLET - TRAVERSE

15448420000		P245/70R17 108S SL	Grabber HTS	BSW			09	10	11	12	13	
-------------	--	--------------------	-------------	-----	--	--	----	----	----	----	----	--

DODGE - RAM 3500

04566420000	X	LT235/80R17 120/117R E	AmeriTrac TR	OWL	04501870000	AmeriTrac TR	09	10	11	12		
04501870000		LT235/80R17 120/117R E	AmeriTrac TR	OWL							12	13
04566430000		LT235/80R17 120/117R E	AmeriTrac TR	BSW			09	10	11	12		
04501880000		LT235/80R17 120/117R E	AmeriTrac TR	BSW							12	13
04566450000		LT235/80R17 120/117R E	AmeriTrac	BSW			09	10	11	12		
04501890000		LT235/80R17 120/117R E	AmeriTrac	BSW								13

FORD - F150

04563450000	X	LT245/70R17 114/110S D	Grabber Tr	BSW	04571080000	Grabber TR	09	10				
15448240000		P255/70R17 110S SL	AmeriTrac TR	BSW			09	10				

FORD - F250/350

04569450000		LT245/75R17 121/118S E	Grabber HTS	BSW						11		13
04569460000		LT275/65R18 123/120S E	Grabber HTS	BSW						11		

GMC - CANYON

15448880000	X	P215/70R16 99S SL	Ameri*GS60	BSW	15449050000	Grabber HTS	09					
15449050000		P215/70R16 99S SL	Grabber HTS	BSW			09	10	11	12		

***ARTICLE NUMBER FITS OE VEHICLE REFERENCED

Continued next page

ARTICLE NUMBER	DISCONTINUED	SIZE & SPEED/LOAD INDEX	TIRE NAME	SIDEWALL	***ALTERNATIVE FITMENT	***ALTERNATIVE TIRE LINE	YEAR SELECTED AS OE
----------------	--------------	-------------------------	-----------	----------	------------------------	--------------------------	---------------------

GMC - SAVANA

04501160000		LT215/85R16 115/112S E	AmeriTrac	BSW					10	11		
04568620000	X	LT215/85R16 115/112S E	AmeriTrac	BSW	no replacement		09	10				
04501200000		LT225/75R16 115/112S E	Grabber HTS	BSW						11	12	13
15448380000		P245/70R17 108S SL	AmeriTrac	BSW			09	10	11	12	13	
15448430000	X	P245/70R17 108S SL	AmeriTrac	OWL	15448720000	Grabber HTS	09					

GMC - SIERRA

04569100000		LT225/75R17 116/113Q E	Grabber AW	BSW			09	10				
04569260000		LT225/75R17 116/113Q E	Grabber TR	BSW			09	10				
15449020000		P245/70R17 108H SL	AmeriTrac	BSW					10	11	12	13
15476370000	X	P245/70R17 108H SL	AmeriTrac	BSW	15449020000	AmeriTrac	09	10				
15448410000	X	P245/70R17 108S SL	AmeriTrac	BSW	15449490000	Grabber HTS	09	10				
15484700000	X	P245/70R17 108S SL	AmeriTrac	BSW	15449490000	AmeriTrac		10				
15449490000		P245/70R17 108T SL	Grabber HTS	BSW			09	10			12	13
15448890000	X	P265/70R17 113H SL	AmeriTrac TR	BSW	15482850000	AmeriTrac TR	09	10				

NISSAN - FRONTIER

15486010000		225/70R15 100T	Grabber HTS	OWL							12	13
15480030000		P235/75R15 105S SL	Grabber AW	BSW			09	10	11	12	13	
15473840000		P265/70R16 111S SL	Grabber AW	BSW			09	10	11			
15473840000		P265/70R16 111S SL	Grabber AW	BSW			09	10	11			

NISSAN - PATHFINDER

15473830000		P245/75R16 109S SL	Grabber AW	BSW			09	10	11	12		
-------------	--	--------------------	------------	-----	--	--	----	----	----	----	--	--

SUZUKI - EQUATOR

15480030000		P235/75R15 105S SL	Grabber AW	BSW			09	10	11	12	13	
-------------	--	--------------------	------------	-----	--	--	----	----	----	----	----	--

***ARTICLE NUMBER FITS OE VEHICLE REFERENCED

LIMITED WARRANTY AND ADJUSTMENT POLICY

(See Warranty Brochure for complete details)

Eligibility

- Purchased as replacement tires only.
- Owner of General brand passenger/LT or special/temporary spare tires.
- Tires used on vehicle originally installed.

Coverage

All General Passenger Tires

- Free replacement during 12 months from date of purchase OR first 2/32 treadwear (whichever comes first – mounting and balancing included).
- Pro-rated after free replacement period up to 72 months from date of purchase or wear-out (whichever comes first – mounting and balancing NOT included).

General Temporary spare Tire

- Free replacement within first 1/32nds of treadwear.
- After free replacement period no adjustment made.

Not Covered

- Road Hazards.
- Repairs.
- Damage resulting from improper maintenance or operation.
- Damage resulting from vehicle mechanical problems.
- Ride/vibration after 2/32nds of treadwear or 12 months (whichever comes first).
- Wear due to improper vehicle alignment.
- Commercial applications.

Customer

- Responsible for all applicable taxes and local tire disposal fees.
- Must have invoice with date of purchase (DOT tire identification number and/or date of manufacture will be used if invoice not available).

LIMITED TREAD WEAR-OUT COVERAGE

(See Warranty Brochure for complete details)

Eligibility

- Purchased as replacement tires only.
- Tires used on vehicle originally installed.

Products

- GMAX™ AS-03
 - 40,000 miles
- Altimax™ HP (H)
 - 55,000 miles
- Altimax™ HP (V)
 - 40,000 miles
- Altimax™ RT
 - 70,000 miles
- Grabber™ HTS
 - 60,000 miles limited treadwear warranty (Includes Metric and P-Metric sizes with speed ratings of T and below),
 - 45,000 miles limited treadwear warranty (Includes all Metric sizes with speed ratings of H and above and all LT Metric sizes)

Grabber™ AT2

- 60,000 miles (excludes LT and floatation sizes)

Coverage

- Pro-rated replacement for wearout during mileage coverage OR 72 months of service (whichever comes first).
- Mounting and balancing NOT included.
- Pro rated price = (mileage received/mileage covered) x dealer selling price = customer price.
- Mileage Warranty for the rear axle of split fitments will be 50% of the standard tread wearout coverage.

Not Covered

- Road Hazards or repairs.
- Commercial applications.
- Damage resulting from improper maintenance or operation.
- Damage resulting from vehicle mechanical problems.
- Tires not rotated every 6,000 - 8,000 miles.
- Tires in service more than 72 months.

Customer

- Must have original, up-to-date copy of the Tread Wearout Coverage Rotation Schedule (printed in Limited Warranty Brochure) showing rotation intervals and odometer reading at installation and wear-out.
- Must have original sales invoice with date of purchase.
- Pays for mounting, balancing, and all applicable taxes and local tire disposal fees.

PASSENGER TIRE AND LIGHT TRUCK DEPTH CONVERSION TABLE TO PERCENTAGE OF WEAR:

All numbers to the right designate the percentage of usable tread remaining, used to determine credit due to customer toward the purchase of a replacement tire. The numbers to the left designate the percentage of usable tread worn, to determine customer's charge for a replacement tire.

To obtain the remaining tread depth, take three (3) measurements around the tire and average. Locate (below) the tire's original tread depth. Read down and across matching the tire's measured remaining tread depth. Use the percentages shown as a charge and/or credit towards the purchase of a replacement tire.

ORIGINAL TIRE TREAD DEPTHS IN 32NDS

	9/32	10/32	11/32	12/32	13/32	14/32	15/32	16/32	17/32	18/32	19/32	20/32	21/32	22/32	23/32	24/32	25/32	26/32	27/32	28/32
Remaining Tread																				
2/32	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0
3/32	86%/14	88%/12	89%/11	90%/10	91%/9	92%/8	92%/8	93%/7	93%/7	94%/6	94%/6	94%/6	95%/5	95%/5	95%/5	95%/5	96%/4	96%/4	96%/4	96%/4
4/32	71%/29	75%/25	78%/22	80%/20	82%/18	83%/17	85%/15	86%/14	87%/13	88%/12	88%/12	89%/11	89%/11	90%/10	90%/10	91%/9	91%/9	92%/8	92%/8	92%/8
5/32	57%/43	63%/37	67%/33	70%/30	73%/27	75%/25	77%/23	79%/21	80%/20	81%/19	82%/18	83%/17	84%/16	85%/15	86%/14	86%/14	87%/13	88%/12	88%/12	88%/12
6/32	43%/57	50%/50	56%/44	60%/40	64%/36	67%/33	69%/31	71%/29	73%/27	75%/25	76%/24	78%/22	79%/21	80%/20	81%/19	82%/18	83%/17	83%/17	84%/16	85%/15
7/32	29%/71	38%/62	44%/56	50%/50	55%/45	58%/42	62%/38	64%/36	67%/33	69%/31	71%/29	72%/28	74%/26	75%/25	76%/24	77%/23	78%/22	79%/21	80%/20	81%/19
8/32	14%/86	25%/75	33%/67	40%/60	45%/55	50%/50	54%/46	57%/43	60%/40	63%/37	65%/35	67%/33	68%/32	70%/30	71%/29	73%/27	74%/26	75%/25	76%/24	77%/23
9/32	0%/100	13%/87	22%/78	30%/70	36%/64	42%/58	46%/54	50%/50	53%/47	56%/44	59%/41	61%/39	63%/37	65%/35	67%/33	68%/32	70%/30	71%/29	72%/28	73%/27
10/32		0%/100	11%/89	20%/80	27%/73	33%/67	38%/62	43%/57	47%/53	50%/50	53%/47	56%/44	58%/42	60%/40	62%/38	64%/36	65%/35	67%/33	68%/32	69%/31
11/32			0%/100	10%/90	18%/82	25%/75	31%/69	36%/64	40%/60	44%/56	47%/53	50%/50	53%/47	55%/45	57%/43	59%/41	61%/39	62%/38	64%/36	65%/35
12/32				0%/100	9%/91	17%/83	23%/77	29%/71	33%/67	37%/63	41%/59	44%/56	47%/53	50%/50	52%/48	55%/45	57%/43	58%/42	60%/40	62%/38
13/32					0%/100	8%/92	15%/85	21%/79	27%/73	31%/69	35%/65	39%/61	42%/58	45%/55	48%/52	50%/50	52%/48	54%/46	56%/44	58%/42
14/32						0%/100	8%/92	14%/86	20%/80	25%/75	29%/71	33%/67	37%/63	40%/60	43%/57	45%/55	48%/52	50%/50	52%/48	54%/46
15/32							0%/100	7%/93	13%/87	19%/81	24%/76	28%/72	32%/68	35%/65	38%/63	41%/59	43%/57	46%/54	48%/52	50%/50
16/32								0%/100	7%/93	12%/88	18%/82	22%/78	26%/74	30%/70	33%/67	36%/64	39%/61	42%/58	44%/56	46%/54
17/32									0%/100	6%/94	12%/88	17%/83	21%/79	25%/75	29%/71	32%/68	35%/65	38%/62	40%/60	42%/58
18/32										0%/100	6%/94	11%/89	16%/84	20%/80	24%/76	27%/73	30%/70	33%/67	36%/64	38%/62
19/32											0%/100	6%/94	11%/89	15%/85	19%/81	23%/77	26%/74	29%/71	32%/68	35%/65
20/32												0%/100	5%/95	10%/90	14%/86	18%/82	22%/78	25%/75	28%/72	31%/69
21/32													0%/100	5%/95	10%/90	14%/86	17%/83	21%/79	24%/76	27%/73
22/32														0%/100	5%/95	9%/91	13%/87	17%/83	20%/80	23%/77
23/32															0%/100	5%/95	9%/91	12%/88	16%/84	19%/81
24/32																0%/100	4%/96	8%/92	12%/88	15%/85
25/32																	0%/100	4%/96	8%/92	12%/88
26/32																		0%/100	4%/96	8%/92
27/32																			0%/100	4%/96
28/32																				0%/100



• Dot shows location to make tread depth remaining measurement.

30/45 Day Customer Satisfaction Trial

(See Warranty Brochure for complete details)

Eligibility

- Purchased as replacement tires only.
- Tires used on vehicle originally installed.

Products

- Original Purchaser of a set of four (4) General brand tires.
- Used on vehicle originally installed.
- Must complete information section in brochure.

Coverage

- Original Purchased set of four (4) tires.
- Within 30 days from date of purchase return and exchange all or any one for any reason except for service related conditions. (45 days for GMAX™ AS-03, Altimax™ RT, HP, and Grabber™ HTS).
- If exchanged for higher priced tire, customer pays the difference.

- If exchanged for lower priced tire, customer receives refund.

Not Covered

- Road Hazards or repairs.
- Commercial applications.
- Damage resulting from improper maintenance or operation.
- Damage resulting from vehicle mechanical problems.
- Improper mounting or demounting.
- Alterations.

Customer

- Pays for valve stems if required.
- Responsible for all applicable taxes for higher cost tire.
- Must have completed brochure information section.



**FOR LIMITED WARRANTY
AND ADJUSTMENT POLICY
AND SAFETY AND MAINTENANCE
INFORMATION WE ENCOURAGE
YOU TO VISIT OUR WEBSITE AT
WWW.GENERALTIRE.COM
(CUSTOMER CARE LINK).**

**FOR ADDITIONAL SAFETY AND
MAINTENANCE INFORMATION,
PLEASE ALSO VISIT THE RUBBER
MANUFACTURER ASSOCIATION (RMA)
WEBSITE AT WWW.RMA.ORG.**

**TO ORDER HARD COPIES
OF OUR WARRANTY BROCHURES,
PLEASE CONTACT THE ADVERTISING
ORDER DESK AT 1-888-287-5513 (IN THE US)
OR 1-800-461-1776 (IN CANADA).**

**INSIDE SALES: 1-800-321-7575
CONSUMER RELATIONS: 1-800-847-3349**

AFTER THE SALE, DID YOU COMPLETE YOUR OBLIGATION UNDER THE LAW?

THE NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION (NHTSA) REGULATES THE USE OF TIRE REGISTRATION FORMS BY TIRE MANUFACTURERS AND TIRE DEALERS/DISTRIBUTORS, 49 CFR 574, ET SEQ.. TIRE MANUFACTURERS ARE REQUIRED TO PROVIDE TIRE REGISTRATION FORMS TO ITS TIRE DEALERS/DISTRIBUTORS. TIRE DEALERS/DISTRIBUTORS WHO SELL DIRECTLY TO CONSUMERS ARE REQUIRED TO PROVIDE TIRE REGISTRATION FORMS TO CONSUMERS AT THE TIME OF SALE. TIRE DEALERS/DISTRIBUTORS ARE ALSO REQUIRED TO SUPPLY TIRE REGISTRATION FORMS TO OTHER DEALERS FOR RESALE (OR "RESELLERS").

WHEN COMPLETING AND MAILING THE TIRE REGISTRATION FORMS, IT IS VERY IMPORTANT THAT YOU LIST ALL OF THE INFORMATION COMPLETELY AND ACCURATELY FOR THE REASONS STATED ABOVE. PLEASE FILL OUT THE SHADED AREAS OF THE TIRE REGISTRATION FORM (SEE EXAMPLE BELOW) AND INCLUDE THE NAME OF THE DEALER/DISTRIBUTOR, ADDRESS, QUANTITY OF TIRES SOLD, AND THE COMPLETE D.O.T. TIRE IDENTIFICATION NUMBER FOR THE TIRE(S) SOLD. IF YOU ASSIST THE CONSUMER IN COMPLETING AND MAILING THE REGISTRATION FORMS, LIST HIS OR HER FULL NAME, COMPLETE ADDRESS SECTION, APPLY SUFFICIENT POSTAGE AND MAIL. YOU MAY ALSO REGISTER YOU TIRES ONLINE BY VISITING OUR WEBSITE AT WWW.GENERALTIRE.COM AND CLICKING ON THE "REGISTER YOUR TIRES" TAB.

IF YOU DO NOT COMPLETE AND MAIL THE REGISTRATION FORM FOR THE CUSTOMER, PLEASE FILL OUT THE SHADED AREAS OF THE TIRE REGISTRATION FORM (SEE EXAMPLE BELOW) AND INCLUDE THE NAME OF THE DEALER/DISTRIBUTOR, ADDRESS, QUANTITY OF TIRES SOLD, AND THE COMPLETE D.O.T. TIRE IDENTIFICATION NUMBER FOR THE TIRE(S) SOLD. THEN THE CUSTOMER ENTERS HIS OR HER NAME AND ADDRESS ON THE FORM, APPLY POSTAGE AND MAIL THE FORM.

PENALTIES

FAILURE TO COMPLY WITH THESE REQUIREMENT MAY RESULT IN CIVIL PENALTIES OF \$5,000 FOR EACH VIOLATION AND UP TO A MAXIMUM OF \$15,000,000.

YOU MAY CONTACT OUR CUSTOMER RELATIONS DEPARTMENT AT 1-800-847-3349 (IN THE US) OR 1-800-461-1776 (IN CANADA) IF YOU HAVE QUESTIONS ABOUT TIRE REGISTRATION.

REMEMBER, COMPLETE YOUR OBLIGATIONS UNDER THE LAW.

IMPORTANT

In case of a recall, we can reach you only if we have your name and address. You **MUST** send in this card to be on our recall list.

DO IT TODAY! Date of Sale ___/___/___

OMB Approved OMB No. 2127-0050
Shaded Areas Must Be Filled In By Seller

Register **ONLY** tire brand checked ✓ below

CONTINENTAL TIRE
 GENERAL TIRE

SELLER COMPLETE

Qty.	TIRE IDENTIFICATION NUMBERS											
	1	2	3	4	5	6	7	8	9	10	11	12

SELLER COMPLETE (Can be Rubber Stamped)

SELLER'S NAME

SELLER'S ADDRESS

CITY STATE/PROVINCE ZIP/POSTAL CODE

CUSTOMER'S NAME (Please print)

CUSTOMER'S ADDRESS

CITY STATE/PROVINCE ZIP/POSTAL CODE

Federal law restricts above information provided to be used for tire recall purposes only!

CTA, LLC
PO BOX 5000
FORT MILL, SOUTH CAROLINA 29716
www.generaltire.com
Inside Sales: 1.800.321.7575
Consumer Relations: 1.800.847.3349

Item # PR-PLTGEN 1/13

follow us:

