



TURNPIKE USA

TURNPIKE USA



PARRISH TIRE COMPANY

5130 Indiana Avenue
Winston-Salem, NC 27106

1-800-849-8473
www.parrishtire.com

**RADIAL TRUCK
& BUS TIRES**

DRIVE THE WORLD.

PARRISHTIRE.COM

S600

Low Noise, Long Mileage Drive



Applications:

Long haul, over-the-highway steering and all-position use.

- Five-Rib Tread Design provides superior water channel dispersion and long tread life.
- 19/32" Tread Depth delivers extended removal mileage.
- Stress wear control groove reduces the occurrence of shoulder step-down wear by redistributing the load on the outside of the rib.

D880

Deep Tread, On & Off Road Use



Applications:

Construction Service, On/Off Highway, Drive Position.

- Extra deep tread design for on and off road applications.
- Chip and cut resistant compound to avoid snags and tears.

Tire Sizes	Ply Rating	Speed Symbol	Tread Depth		Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim												Tire Sizes	Ply Rating	Speed Symbol	Tread Depth		Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim
-	-	-	MM	32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-												-	-	-	MM	32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-
11R22.5	14	M	15.0	19	144/142	2800/2650(6175/5840)	279	1050	720(105)	8.25												11R22.5	16	M	25.5	32	146/143	3000/2725(6610/6005)	279	1050	830(120)	8.25
11R22.5	16	M	15.0	19	146/143	3000/2725(6610/6005)	279	1050	830(120)	8.25												11R24.5	16	M	25.5	32	149/146	3250/3000(7160/6610)	279	1104	830(120)	8.25
11R24.5	14	M	15.0	19	146/143	3000/2725(6610/6005)	279	1104	720(105)	8.25																						
11R24.5	16	L	15.0	19	149/146	3250/3000(7160/6610)	279	1104	830(120)	8.25																						
95/75R22.5	14	M	15.0	19	144/141	2800/2575(6175/5675)	298	1014	760(110)	9																						
95/75R22.5	16	L	15.0	19	146/143	3000/2725(6610/6005)	298	1014	830(120)	9																						
85/75R24.5	14	M	15.0	19	144/141	2800/2575(6175/5675)	283	1050	760(110)	8.25																						
85/75R24.5	16	L	15.0	19	147/144	3075/2800(6780/6175)	283	1050	830(120)	8.25																						

DRIVE THE WORLD.

TURNPIKE

S500

Superior Stability and Safety



Applications:

High speed trailer wheel with great stability.

- Superior stability and safety with center lines.
- Applicable for high speed trailer wheel.

S900

High Speed, Heavy Load Trailer



Applications:

Front and trailer wheels, with ultimate traction.

- Designed for front and trailer wheels.
- Super traction and braking performance.
- Heavy load and high speed capability.

Tire Sizes	Ply Rating	Speed Symbol	Tread Depth		Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim												Tire Sizes	Ply Rating	Speed Symbol	Tread Depth		Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim
-	-	-	MM	32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-												-	-	-	MM	32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-
15/75R17.5	14	M	12.1	15	126/124	1700/1600(3750/3530)	211	767	700(101)	6												275/80R22	16	M	16.0	20	144/1496	3250/3000(7165/6620)	276	1012	850(123)	8.25
15/75R17.5	16	J	12.1	15	135/133	2180/2060(4805/4540)	211	767	865(125)	6												295/80R22	16	M	16.0	20	152/148	3550/3150(7830/6945)	298	1044	850(123)	9
15/75R17.5	16	L	12.6	16	132/130	2000/1900(4410/4190)	233	797	775(112)	6.75												315/80R22	18	M	16.0	20	154/150	3750/3350(8270/7380)	312	1076	830(120)	9
15/75R17.5	18	J	12.6	16	143/141	2725/2575(6005/5675)	233	797	865(125)	6.75												315/80R22	20	K	16.0	20	156/150	4000/3350(8820/7380)	312	1076	870(125)	9
15/70R19.5	14	L	12.1	15	128/126	1800/1700(3970/3750)	226	811	760(110)	6.75												12R22.5	18	M	16.0	20	152/148	3550/3150(7830/6945)	300	1084	850(123)	9
15/70R19.5	16	L	12.6	16	135/133	2180/2060(4805/4540)	248	839	830(120)	7.5												11.00R22	18	L	16.0	20	154/151	3750/3450(8270/7610)	293	1135	900(134)	8
15/70R19.5	16	L	13.5	17	143/141	2725/2575(6010/5680)	262	867	790(115)	7.5																						
15/70R22.5	16	L	13.1	17	140/137	2500/2300(5510/5070)	255	930	830(120)	7.5																						
15/70R22.5	16	L	14.1	18	148/145	3150/2900(6940/6395)	276	958	900(130)	8.25																						
15/65R22.5	20	K	16.5	20	160	4500(9920)	389	1072	900(120)	11.75																						
15/65R22.5	20	K	16.5	21	165	5150(11350)	430	1124	900(120)	13																						

DRIVE THE WORLD.

TURNPIKE

D660

High Speed, Long Mileage Drive



Applications:

Tandem drive axle to long and short over-the-highway use.

- 28/32" closed shoulder tread design provides even tread wear and optimized mileage while still providing excellent traction.
- Innovative groove technology minimizing stone retention, providing excellent retread services and reduced casing penetrations.
- High carrying capacity and extra tough tread elements take this tire to the next level of severe service durability.

S700

High Speed, Low Noise Drive



Applications:

Long haul, over-the-highway steering and all-position use.

- The pattern is designed for long mileage.
- Applicable for high speed and lower noise.

Tire Sizes	Ply Rating	Speed Symbol	Tread Depth		Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim
-	-	-	MM	32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-

11R22.5	14	M	22.5	28	144/142	2800/2650(6175/5840)	279	1050	720(105)	8.25
11R22.5	16	M	22.5	28	146/143	3000/2725(6610/6005)	279	1050	830(120)	8.25
11R24.5	14	M	22.5	28	146/143	3000/2725(6610/6005)	279	1104	720(105)	8.25
11R24.5	16	L	22.5	28	149/146	3250/3000(7160/6610)	279	1104	830(120)	8.25
295/75R22.5	14	M	22.5	28	144/141	2800/2575(6175/5675)	298	1014	760(110)	9
295/75R22.5	16	L	22.5	28	146/143	3000/2725(6610/6005)	298	1014	830(120)	9
285/75R24.5	14	M	22.5	28	144/141	2800/2575(6175/5675)	283	1050	760(110)	8.25
285/75R24.5	16	L	22.5	28	147/144	3075/2800(6780/6175)	283	1050	830(120)	8.25

Tire Sizes	Ply Rating	Speed Symbol	Tread Depth		Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim
-	-	-	MM	32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-

315/80R22.5	18	M	15.0	19	154/150	3750/3350(8270/7380)	312	1076	830(120)	9
315/80R22.5	20	K	15.0	19	160/157	4540/4125(10000/9090)	312	1076	900(130)	9

DRIVE THE WORLD.

TURNPIKE USA

D770

High Speed, Long Mileage Drive



Applications:

High speed wheels for short or long hauls.

- Applicable for driving wheels.
- Applicable for high speed and long mileage.

TB878

High Speed, Powerful Driving



Applications:

Made for high speeds with powerful driving force.

- Designed combination pattern for all wheels of bus and trucks.
- Strong damage and wear resistance.
- Applicable for high speed, long mileage and powerful driving force.

Tire Sizes	Ply Rating	Speed Symbol	Tread Depth	Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim	Tire Sizes	Ply Rating	Speed Symbol	Tread Depth	Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim
-	-	-	MM 32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-	-	-	-	MM 32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-

315/80R22.5	18	M	22.0	27.7	154/150	3750/3350(8270/7380)	312	1076	830(120)	9
315/80R22.5	20	K	22.0	27.7	160/157	4540/4125(10000/9090)	312	1076	900(130)	9
12R22.5	16	M	22.0	27.7	152/148	3550/3150(7830/6945)	300	1084	850(123)	9

9.00R20	16	L	15.5	20.0	144/142	2800/2650(6180/5850)	259	1019	900(130)	7
10.00R20	18	L	16.5	21.0	149/146	3250/3000(7160/6610)	278	1054	930(135)	7.5
11.00R20	18	L	17.0	21.5	152/149	3550/3250(7830/7170)	293	1085	930(135)	8
12.00R20	18	L	17.5	22.0	154/151	3750/3450(8270/7610)	315	1125	830(120)	8.5
13R22.5	18	K	18.1	23.0	156/150	4000/3350(8810/7380)	320	1124	875(127)	9.75

DRIVE THE WORLD.

TURNPIKE

S650

Low Resistance, Heavy Load Trailer



Applications:

Long haul, heavy load trailer wheels.

- Designed for trailer wheels.
- Light weight and lower rolling resistance.
- Heavy load and high speed capability.

D990

High Speed, Heavy Load Drive



Applications:

Long haul, heavy load driving wheels.

- Designed for driving wheels.
- With extra grip performance.
- Super traction and braking performance.
- Heavy load and high speed capability.

Tire Sizes	Ply Rating	Speed Symbol	Tread Depth		Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim	Tire Sizes	Ply Rating	Speed Symbol	Tread Depth		Load Index	Max. Load	Section Width	Overall Diameter	Max. Load	Std. Rim
-	-	-	MM	32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-	-	-	-	MM	32NDs	S/D	S/Dkg(LBs)	MM	MM	KPA(PSI)	-
11R22.5	14	M	10.5	13.2	144/142	2800/2650(6175/5845)	279	1050	720(105)	8.25	295/80R22.5	16	M	22	27.7	152/148	3550/3150(7830/6945)	298	1044	850(123)	9
11R24.5	14	M	10.5	13.2	146/143	3000/2725(6610/6010)	279	1104	720(105)	8.25	315/80R22.5	18	M	22	27.7	154/150	3750/3350(8270/7380)	312	1076	830(120)	9
295/75R22.5	14	M	10.5	13.2	144/141	2800/2575(6175/5680)	298	1014	760(110)	9	315/80R22.5	20	L	22	27.7	156/150	4000/3350(8820/7380)	312	1076	870(125)	9
285/75R24.5	14	M	10.5	13.2	144/141	2800/2575(6175/5680)	283	1050	760(110)	8.25	12R22.5	18	M	22	27.7	152/148	3550/3150(7830/6945)	300	1084	850(123)	9
											11.00R22	18	L	22	27.7	154/151	3750/3450(8270/7610)	293	1135	900(134)	8
											1000R20	18	L	22	27.7	149/146	3250/3000(7610/6610)	278	1055	930(134)	7.5

DRIVE THE WORLD.

TURNPIKE